

**QUICK CAB PCQ 404017 G**



Sample photo

**Order symbol:** CAB PCQ 404017 G  
**Product nbr:** 8113488  
**Description:** Cabinet, PC  
**Remarks:** Grey cover

**EAN:** 6418074011183  
**EI. number:**  
 Finland: 3421982  
 Electric No. Italy: 7681050  
 Electric No. Sweden: 2540101

Including: Base with screws for mounting plate/DIN-rail, internal corner plugs, cover with PUR gasket and CS 12137 cover screws.

Dimensions:		Length	Width	Height	Accessories:	
mm:		400	400	170	EKIV 37	DIN-35 Mounting rail
inch:		15.7	15.7	6.7	FP A 44	Swing-out door/Front plate
Materials:					MB 12225 AL	Swing door set
<b>Material:</b>		Polycarbonate			FP 18x2-44	Front plate
<b>Base colour:</b>		RAL 7035 -light grey			EKI EXT 44	Extension frame
<b>Cover screws material:</b>		Polyamide			DRF 43/44	DIN rail frame set
<b>Cover colour:</b>		RAL 7035 -light grey			PAT 12040	Hinge set
<b>Cover screws colour:</b>		RAL 5023			Rating:	
<b>Gasket material:</b>		Polyurethane			Ingress Protection (EN 60529):	IP66/IP67
Temperatures:					Impact Resistance (EN 62262):	IK08
<b>Temperature °C (short term):</b>		-40 ... 120 °C			Electrical insulation:	Totally insulated
<b>Temperature °C (continuous):</b>		-40 ... 80 °C			Halogen free (DIN/VDE 0472, Part 815):	1
<b>Temperature °F (short term):</b>		-40 ... 250 °F			UV resistance:	UL 508
<b>Temperature °F (continuous):</b>		-40 ... 175 °F			Flammability Rating:	UL 746C 5"
Accessories:					Glow Wire Test (IEC 695-2-1) °C:	960
EKIV 44	Mounting plate				NEMA Class:	NEMA 1, 4, 4X, 12, 13
Certificates:					Germanischer Lloyd (GL)	
					SGS Fimko	
					Lloyds Register of Shipping (LR)	
					Gost R	

