Product data sheet Characteristics

NSYTBS775

ABS box IP66 IK07 RAL7035 Int.H65W65D45 Ext.H74W74D56 Opaque cover H10



Main Range Thalassa TBS Device application Multi-purpose Category Industrial box Height 74 mm 74 mm Width 54 mm Depth Internal height 65 mm 65 mm Internal width Internal depth 47 mm Enclosure mounting Wall mounted Device composition 4 x cover screw 1 x cover 1 x body Set of 5 Quantity per set Body type One piece moulded Type of front cover Low plain cover

Metal screws

Cover, by captive screws

Outside sealed area: flat screwdriver captive screw

Complementary

o in promoting y		
Material	ABS	
Colour	Grey (RAL 7035)	
Standards	IEC 62208	
Product certifications	DEMKO SEMKO TÜV	
IP degree of protection	IP66conforming to NEMA 4.4X	
IK degree of protection	IK07conforming to IEC 62262	
Fire resistance	650 °C conforming to IEC 60695-2-11	
Ambient air temperature for storage	-1540 °C	
Operating temperature	-2560 °C	

Cover fixing

Removable parts

Lock type

Offer Sustainability

Not Green Premium product
Compliant - since 0940 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold
Need no specific recycling operations