

## Medium Industrial

### AB aluminium - rubber

*Wielen met aluminiumkern - zwarte gevulkaniseerde rubberband 72° Shore A – 2 standaard kogellagers*

*Roues avec noyau aluminium - bandage caoutchouc noir vulcanisé 72° Shore A – 2 roulements à billes standards*

*Wheels with an aluminium centre - black vulcanized rubber tyre 72° Shore A – 2 standard ball bearings*

*Räder mit Aluminiumradkörper - schwarze vulkanisierte Gummibereifung 72° Shore A – 2 Standard Kugellager*



mm



mm



mm



mm



kg



Ø

WTAB 1002 6150	100	40	50	15	180	10
WTAB 1252 6150	125	38	50	15	200	10
WTAB 1503 6440	150	50	62	20	300	12
WTAB 1603 6440	160	50	62	20	350	12
WTAB 2003 6440	200	50	62	20	450	12

### bolt hole



mm



mm



mm



mm



kg

JTAB 1005 6150	BTAB 1005 6150	100	12	128	40	134	180
JTAB 1255 6150	BTAB 1255 6150	125	12	155	42,5	134	200

**top plate**



JTAB 1002 6150	BTAB 1002 6150	FTAB 1002 6150	100	105 x 88	80 x 60	8,5	128	40	134	180
JTAB 1252 6150	BTAB 1252 6150	FTAB 1252 6150	125	105 x 88	80 x 60	8,5	155	42,5	134	200
JTAB 1253 6150	BTAB 1253 6150	FTAB 1253 6150	125	135 x 110	105 x 75/80	10,5	155	42,5	134	200
JTAB 1503 6440	BTAB 1503 6440	FTAB 1503 6440	150	135 x 110	105 x 75/80	10,5	188	53	160	300
JTAB 1603 6440	BTAB 1603 6440	FTAB 1603 6440	160	135 x 110	105 x 75/80	10,5	193	53	160	350
JTAB 2003 6440	BTAB 2003 6440	FTAB 2003 6440	200	135 x 110	105 x 75/80	10,5	238	53	160	450



- zwenkwiel met richtingsvastzetting – enkel voor wielen diameter 100 – 125 mm
- roulette avec blocage directionnel – uniquement sur roues diamètre 100 – 125 mm
- swivel castor with directional lock – only on wheels diameter 100 – 125 mm
- Rad mit Richtungsfeststeller – nur auf Rädern Durchmesser 100 – 125 mm

**CODE:** (D)TAB 1002 6150