



## 1. General description

Indelible paint. Industrial use only.

## 2. Features

- For all types of surfaces.
- Functions on wet, oily, greasy and rusted surfaces.
- UV resistant.
- Excellent water resistance.
- Functional over a wide temperature range.

## 3. Applications

- Steel construction.
- Ship repair.
- Building and civil engineering.
- Topographic surveys.

## 4. Directions

• A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.

## 5. Typical product data (without propellant)

Appearance	Not available.
Color	See color cap.
Odor	Characteristic odor.
Density	< 1.0 g/cm <sup>3</sup> (@ 20°C).
Application temperature	-20 to +70 °C
Operating temperature active product	max 200 °C

## 6. Packaging

TU 10x50 ML



Manufactured by :  
**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele Belgium  
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)





Technical data sheet  
**MARKER BALL**

Reference : 30158 - 30163

---

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com) We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC\_GREEN-MARKER\_BALL-20111202

Date



Manufactured by :  
**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele Belgium  
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34  
**www.crcind.com**

