



Technical Data Sheet

HTG High Temperature Grease

Product Description

HTG is specifically designed for use in many mechanical and electrical applications operating at high temperatures. The product has excellent lubrication properties and contains anti-rust and anti-wear properties.

Features

- Wide operating temperature range.
- Safe on most thermoplastics.
- Water resistant
- Low evaporation weight loss

Approvals **RoHS Compliant (2002/95/EC):** **Yes**

Typical Properties:

Colour	Light Brown
Temperature Range (°C)	-20 to +200
Evaporation Weight Loss (% 7 days @ 125°C)	3.1
Drop Point (IP32 / ISO 2176 (°C))	>250
Cone Penetration Un-worked (ASTM D 217 @ 20°C)	275
Thickener	Clay
Thermal Conductivity (W/mK)	0.4
UV Trace	No

Electrical Properties:

Dielectric Strength	35
---------------------	----

Base Oil Properties:

Base Oil Type	Mineral Oil
Base Oil Viscosity @ 40°C (Kinematic Viscosity (cSt))	465
Pour Point (ASTM D 97 (°C))	-11
Flash Point (COC ASTM D 92 (°C))	230

Mechanical Properties:

4 Ball Wear (mm)	2.261
Weld Load (kgf)	160

Packing

50ml Tube

Order Code

EHTG50T

Shelf Life

48 Months

Directions for Use

HTG should be applied manually.

Typical Product Applications

HTG is suitable for use in many applications where good lubrication and consistent performance at elevated temperatures is required. Examples include photocopier drive systems, laser printer and thermal printer gears, heavy industrial machinery in continuous operation and lubrication of reflow and flow soldering machine chains.

Copyright Electrolube 2011

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.