PRF Bajol

Date 12.6.2017 Previous date: 17.11.2016

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/ UNDERTAKING

1.1 Product identifier

1.1.1 Commercial Product Name

PRF Baiol

1.1.2 Product code

PTBA10L52

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Recommended use

Lubricant

1.3 Details of the supplier of the safety data sheet

1.3.1 Supplier

Taerosol Oy

Street address Hampuntie 21

Postcode and post office 36220

Postcode and post office TelephoneKangasala Finland
03-3565600

Email heikki.jalava@taerosol.com

1.4 Emergency telephone number

1.4.1 Telephone number, name and address

09-471 977 tai 09-4711 Myrkytystietokeskus / HUS PL 340 (Haartmaninkatu 4), 00029 HUS (Helsinki)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Aerosol 1

1272/2008 (CLP)

Aerosol 1, H222

Aerosol 1, H229

Skin Irrit. 2, H315

STOT SE 3, H336

Aquatic Chronic 2, H411

67/548/EEC - 1999/45/EC

F+, Xi, N; R12-38-51/53-67

2.2 Label elements

1272/2008 (CLP)

GHS09 - GHS07 - GHS02 Signal word **Danger**

Hazard Statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.
P262 Do not get in eyes, on skin, or on clothing.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/ 122 °F.

2.3 Other hazards







PRF Bajol

Date 12.6.2017 Previous date: 17.11.2016

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous components

CAS/EC and Reg. number	Chemical name of the substance	Concentratio	n Classification
64742-49-0 265-151-9	Naphtha (petroleum),hydrotreatedlight	30-40%	CLP:Flam.Liq. 2; H225 R 12 Skin.Irrit. 2; H315 R 38 STOT SE 3; H336 R 67 Asp.tox 1; H304 R 65 Aquatic Chronic 2; H411 R 51/53
106-97-8 200-857-2	butan	10-20%	F+; R12; Flam. Gas 1, H220; Press. Gas
74-98-6 200-827-9	propan	10-20%	F+; R12 ;Flam. Gas 1, H220; Press. Gas
	Oil Mixture	20-40%	

3.3 Other information

not determined

4. FIRST AID MEASURES

4.1 Description of first aid measures

Do not induce vomiting: contains petroleum distillates and/or aromatic solvents.

4.1.2 Inhalation

In the case of inhalation of aerosol/mist consult a physician if necessary.

4.1.3 Skin contact

Get medical attention if symptoms occur.

4.1.4 Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

4.1.5 Ingestion

If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard if swallowed - can enter lungs and cause damage.

4.3 Indication of immediate medical attention and special treatment needed

Aspiration hazard

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

5.1.1 Suitable extinguishing media

ABC powder, Carbon dioxide (CO2)

5.1.2 Extinguishing media which must not be used for safety reasons

Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Explosive reaction may occur on heating or burning.

5.3 Advice for firefighters

Alcohol-resistant foam

SAFETY DATA SHEET Page 3/6

PRF Bajol

Date 12.6.2017 Previous date: 17.11.2016

5.4 Specific methods

Immediately evacuate personnel to safe areas.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Prevent unauthorised persons entering the zone. Prevent unauthorised persons entering the zone. Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind.

6.2 Environmental precautions

Prevent product from entering drains.

6.3 Methods and materials for containment and cleaning up

not determined

6.4 Reference to other sections

not determined

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Do not use in areas without adequate ventilation. No sparking tools should be used. Do not taste or swallow. Do not spray on a naked flame or any incandescent material. Do not smoke. Do not empty into drains. Do not store near combustible materials. Take precautionary measures against static discharges. Prevent vapour buildup by providing adequate ventilation during and after use.

7.2 Conditions for safe storage, including any incompatibilities

Do not store near combustible materials. Storage of flammable liquids

7.3 Specific end use(s)

not determined

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

not determined

8.1.1 Threshold limits

64742-49-0	Naphtha(petroleum),	500 ppm (8 h)	630 ppm (15 min)
	hydrotreatedlight	1800 mg/m ³ (8 h)	2300 mg/m ³ (15 min)
106-97-8	butan	800 ppm (8 h)	1000 ppm (15 min)
		1900 mg/m ³ (8 h)	2350 mg/m ³ (15 min)
74-98-6	propan	800 ppm (8 h)	1100 ppm (15 min)
		1500 mg/m ³ (8 h)	2000 mg/m ³ (15 min)

8.1.2 Other information on limit values

not determined

8.1.3 Limit values in other countries

not determined

8.1.4 **DNELs**

not determined

8.1.5 PNECs

not determined

8.2 Exposure controls

8.2.1 Appropriate engineering controls

not determined

8.2.2 Individual protection measures

8.2.2.1 Respiratory protection

SAFETY DATA SHEET Page 4/6

PRF Bajol

Date 12.6.2017 Previous date: 17.11.2016

Provide adequate ventilation. Do not inhale aerosol. Even in case of a full release, due to the small amount of substances present, it is not expected that exposure limits will be reached.

8.2.2.2 Hand protection

It is good practice in industrial hygiene to avoid contact with solvents by using appropriate protective measures whenever possible.

8.2.2.3 Eye/face protection

Avoid contact with the skin and the eyes.

8.2.2.4 Skin protection

Avoid contact with the skin and the eyes.

8.2.3 Environmental exposure controls

not determined

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 9.1.1	Important Health Safety and Environmenta Appearance aerosol	l Information
9.1.2	Odour	hydrocarbon-like
9.1.3	Odour threshold	not determined
9.1.4	рН	7
9.1.5	Melting point/freezing point	-10°C
9.1.6	Initial boiling point and boiling range	< -20 °C
9.1.7	Flash point	< 0 °C
9.1.8	Evaporation rate	not determined
9.1.9	Flammability (solid, gas)	Extremely flammable.
9.1.10	Explosive properties	
9.1.10.1	Lower explosion limit	2,3 til-%
9.1.10.2	Upper explosion limit	9,5 til-%
9.1.11	Vapour pressure	not determined
9.1.12	Vapour density	not determined
9.1.13	Relative density	not determined
9.1.14	Solubility(ies)	
9.1.14.1	Water solubility	insoluble
9.1.14.2	Fat solubility (solvent - oil to be specified)	Soluble in hydrocarbons
9.1.15	Partition coefficient: n-octanol/water	not determined
9.1.16	Auto-ignition temperature	not determined
9.1.17	Decomposition temperature	not determined
9.1.18	Viscosity	not determined
9.1.19	Explosive properties	not determined
9.1.20	Oxidising properties	not determined
9.2	Other information	

10. STABILITY AND REACTIVITY

not determined

10.1 Reactivity

Exposure to sunlight.

10.2 Chemical stability

Stable

SAFETY DATA SHEET Page 5/6

PRF Bajol

Date 12.6.2017 Previous date: 17.11.2016

10.3 Possibility of hazardous reactions

not determined

10.4 Conditions to avoid

Do not expose to temperatures above 50 °C.

10.5 Incompatible materials

not determined

10.6 Hazardous decomposition products

not determined

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

11.1.1 Acute toxicity

LD50/oral/rat =>5840 mg/kg OECD Test Guideline 401

LC50/inhalation/ 4 h/rat =>23.3 mg/LOECDOECD Test Guideline 403

11.1.2 Irritation and corrosion

Irritating to skin.

11.1.3 Sensitisation

not determined

11.1.4 Subacute, subchronic and prolonged toxicity

not determined

11.1.5 STOT-single exposure

Irritating to skin. Vapours may cause drowsiness and dizziness.

11.1.6 STOT-repeated exposure

Prolonged or repeated contact may dry skin and cause irritation.

11.1.7 Aspiration hazard

Aspiration hazard if swallowed - can enter lungs and cause damage.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

12.1.1 Aquatic toxicity

LC50/96h/rainbow trout = 10 < LC/EC

LC50/96h/algae = 10mg/l1

LC50/96h/Sheephead minnows = May cause long-term adverse effects in the aquatic environment.

12.1.2 Toxicity to other organisms

May cause long-term adverse effects in the aquatic environment. Toxic to fish. Toxic to algae.

12.2 Persistence and degradability

12.2.1 Biodegradation

Bioaccumulation is unlikely.

12.2.2 Chemical degradation

Readily biodegradable, according to appropriate OECD test.

12.3 Bioaccumulative potential

Bioaccumulation is unlikely.

12.4 Mobility in soil

not determined

12.5 Results of PBT and vPvB assessment

not determined

12.6 Other adverse effects

not determined

SAFETY DATA SHEET Page 6/6

PRF Bajol

Date 12.6.2017 Previous date: 17.11.2016

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Do not burn, or use a cutting torch on, the empty drum. Dispose of in accordance with local regulations.

13.2 Waste from residues / unused products

not determined

14. TRANSPORT INFORMATION

14.1	UN number	1950
14.2	UN proper shipping name	Aerosols
14.3	Transport hazard class(es)	2.1
14.4	Packing group	-

14.5 Environmental hazards Environmentally hazardous

14.6 Special precautions for users

not determined

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not determined

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

2B - Aerosols

15.2 Chemical safety assessment

not determined

16. OTHER INFORMATION

16.1 Additions, Deletions, Revisions

REGULATION (EC) No 453/2010

16.2 Key or legend to abbreviations and acronyms

not determined

16.3 Key literature references and sources for data

not determined

16.4 Classification procedure

not determined

16.6 Training advice

not determined

16.7 Recommended restrictions

not determined

16.8 Additional information available from:

tilaukset(at)taerosol.com