PRF Silicon

Date 12.6.2017

1.4.1

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/ UNDERTAKING

1.1 1.1.1	Product identifier Commercial Product Name PRF Silicon	
1.1.2	Product code PISILI52	
1.2 1.2.1	Relevant identified uses of the Recommended use Lubricant	substance or mixture and uses advised against
1.3 1.3.1	Details of the supplier of the sa Supplier	fety data sheet
		Taerosol Oy
	Street address Postcode and post office Postcode and post office Telephone Email	Hampuntie 21 36220 Kangasala Finland 03-3565600 heikki.jalava@taerosol.com

1.4 **Emergency telephone number**

Telephone number, name and address 09-471 977 tai 09-4711 Myrkytystietokeskus / HUS PL 340 (Haartmaninkatu 4), 00029 HUS (Helsinki)

2. HAZARDS IDENTIFICATION

2.1	Classification Aerosol 1	of the substance or mixture			
	1272/2008 (C	ΊΡ)			
	Aerosol 1, H222	•			
	Aerosol 1, H22				
	Skin Irrit. 2, H3				
	STOT SE 3, H3				
	Aquatic Chronic				
2.2	Label elemen	ts			
	1272/2008 (0	1272/2008 (CLP)			
	GHS09 - GHS07	7 - GHS02			
	Signal word	Danger C C C C C C C C C C C C C C C C C C C			
	Hazard State	ments			
	H222	Extremely flammable aerosol.			
	H229	Pressurised container: May burst if heated.			
	H315	Causes skin irritation.			
	H336	May cause drowsiness or dizziness.			
	H411	Toxic to aquatic life with long lasting effects.			
	Precautionary	/ Statements			
	P102	Keep out of reach of children.			
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.			
	P211	Do not spray on an open flame or other ignition source.			
	P251	Do not pierce or burn, even after use.			
	P262	Do not get in eyes, on skin, or on clothing.			
	P410+P412	Protect from sunlight. Do no expose to temperatures exceeding 50 °C/ 122 °F.			
22	Other hazard				

Chemical name of the

11 2016

reasons

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous components CAS/EC and Reg. number

Concentration Classification

number	substance		
64742-49-0	Naphtha	30-40%	CLP:Flam.Liq. 2; H225
265-151-9	(petroleum), hydrotreatedlight		R 12
			Skin.Irrit. 2; H315
			R 38
			STOT SE 3; H336
			R 67
			Asp.tox 1; H304
			R 65
			Aquatic Chronic 2; H411
			R 51/53
106-97-8	butan	10-20%	F+; R12
200-857-2			;Flam. Gas 1, H220; Press. Gas
74-98-6	propan	10-20%	F+; R12
200-827-9			;Flam. Gas 1, H220; Press. Gas
63148-62-9	Polydimetyylisiloksan	15-25%	-

4. FIRST AID MEASURES

4.1	Description of first aid measures
	Do not induce vomiting: contains petroleum distillates and/or aromatic solvents.
4.1.2	Inhalation
	In the case of inhalation of aerosol/mist consult a physician if necessary.
4.1.3	Skin contact
	Get medical attention if symptoms occur.
4.1.4	Eye contact
	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
4.1.5	Ingestion
	If swallowed, call a poison control centre or doctor immediately.
4.2	Most important symptoms and effects, both acute and delayed
	Aspiration hazard if swallowed - can enter lungs and cause damage.
4.3	Indication of immediate medical attention and special treatment needed Aspiration hazard

5. FIREFIGHTING MEASURES

5.1	Extinguishing media
5.1.1	Suitable extinguishing media
	ABC powder, Alcohol-resistant foam, Carbon dioxide (CO2)
5.1.2	Extinguishing media which must not be used for safety Do NOT use water jet.
5.2	Special hazards arising from the substance or mixture Explosive reaction may occur on heating or burning.

5.3 Advice for firefighters Alcohol-resistant foam

5.4 Specific methods Immediately evacuate personnel to safe areas.

PRF Silicon

Date 12.6.2017

Previous date: 15.11.2016

6. ACCIDENTAL RELEASE MEASURES

- **6.1 Personal precautions, protective equipment and emergency procedures** Prevent unauthorised persons entering the zone. Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind.
- 6.2 Environmental precautions Prevent product from entering drains.
- 6.3 Methods and materials for containment and cleaning up not determined
- 6.4 Reference to other sections not determined

7. HANDLING AND STORAGE

afe handling

Do not use in areas without adequate ventilation. No sparking tools should be used. Do not taste or swallow. Do not spray on a naked flame or any incandescent material. Do not smoke. Do not empty into drains. Do not store near combustible materials. Take precautionary measures against static discharges. Prevent vapour buildup by providing adequate ventilation during and after use.

- 7.2 Conditions for safe storage, including any incompatibilities
 Do not store near combustible materials. Storage of flammable liquids
 7.2 Specific and use(a)
- 7.3 Specific end use(s) not determined

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Threshold limits

106-97-8	butan	800 ppm (8 h)	1000 ppm (15 min)
		1900 mg/m ³ (8 h)	2350 mg/m ³ (15 min)
74-98-6	propan	800 ppm (8 h)	1100 ppm (15 min)
		1500 mg/m ³ (8 h)	2000 mg/m ³ (15 min)
64742-49-0	Naphtha(petroleum),	500 ppm (8 h)	630 ppm (15 min)
	hydrotreatedlight	1800 mg/m ³ (8 h)	2300 mg/m ³ (15 min)

8.1.2 Other information on limit values

There is no data available for this product.

8.1.3 Limit values in other countries

There is no data available for this product.

8.1.4 DNELs

There is no data available for this product.

8.1.5 PNECs

There is no data available for this product.

8.2 Exposure controls

8.2.1 Appropriate engineering controls not determined

8.2.2 Individual protection measures

8.2.2.1 Respiratory protection

Provide adequate ventilation. Do not inhale aerosol. Even in case of a full release, due to the small amount of substances present, it is not expected that exposure limits will be reached.

8.2.2.2 Hand protection

It is good practice in industrial hygiene to avoid contact with solvents by using appropriate protective measures whenever possible.

SAFETY DATA SHEET

PRF Silicon Date 12.6.2017

8.2.2.3 Eye/face protection

Avoid contact with the skin and the eyes. 8.2.2.4 Skin protection

Avoid contact with the skin and the eyes.

8.2.3 Environmental exposure controls There is no data available for this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 9.1.1	Important Health Safety and Environmenta Appearance aerosol	I Information
9.1.2	Odour	hydrocarbon-like
9.1.3	Odour threshold	not determined
9.1.4	рН	7
9.1.5	Melting point/freezing point	-10°C
9.1.6	Initial boiling point and boiling range	< -20 °C
9.1.7	Flash point	< 0 °C
9.1.8	Evaporation rate	not determined
9.1.9	Flammability (solid, gas)	Extremely flammable.
9.1.10	Explosive properties	
9.1.10.1	Lower explosion limit	2,3 til-%
9.1.10.2	Upper explosion limit	9,5 til-%
9.1.11	Vapour pressure	There is no data available for this product.
9.1.12	Vapour density	There is no data available for this product.
9.1.13	Relative density	There is no data available for this product.
9.1.14 9.1.14.1	Solubility(ies) Water solubility	insoluble
9.1.14.2	Fat solubility (solvent - oil to be specified)	Soluble in hydrocarbons
9.1.15	Partition coefficient: n-octanol/water	There is no data available for this product.
9.1.16	Auto-ignition temperature	There is no data available for this product.
9.1.17	Decomposition temperature	There is no data available for this product.
9.1.18	Viscosity	There is no data available for this product.
9.1.19	Explosive properties	There is no data available for this product.
9.1.20	Oxidising properties	There is no data available for this product.
<u>.</u>		•

9.2 Other information

10. STABILITY AND REACTIVITY

10.1	Reactivity Exposure to sunlight.
10.2	Chemical stability Stable
10.3	Possibility of hazardous reactions There is no data available for this product.
10.4	Conditions to avoid Do not expose to temperatures above 50 °C.
10.5	Incompatible materials

No data is available on the product itself.

PRF Silicon Date 12.6.2017

Previous date: 15.11.2016

10.6 Hazardous decomposition products

No data is available on the product itself.

11. TOXICOLOGICAL INFORMATION

11.1	Information on toxicological effects
11.1.1	Acute toxicity LD50/oral/rat =>5840 mg/kg OECD Test Guideline 401 LC50/inhalation/ 4 h/rat =>23.3 mg/LOECDOECD Test Guideline 403 LD50/dermal/rat ==>2920 mg/kgOECD Test Guideline 402
11.1.2	Irritation and corrosion Irritating to skin.
11.1.3	Sensitisation No data is available on the product itself.
11.1.4	Subacute, subchronic and prolonged toxicity No data is available on the product itself.
11.1.5	STOT-single exposure Irritating to skin. Höyryt voivat aiheuttaa uneliaisuutta ja huimausta.
11.1.7	Aspiration hazard Aspiration hazard if swallowed - can enter lungs and cause damage.
11.1.8	Other information on acute toxicity No data is available on the product itself.

12 FCOLOGICAL INFORMATION

12.	ECC	GIC	NFU	KI'I	411

12.1	Toxicity
12.1.1	Aquatic toxicity
	LC50/96h/rainbow trout =13.4mg/L (OECD 203)

Voi aiheuttaa pitkäaikaisia haittavaikutuksia vesiympäristössä.

12.2 Persistence and degradability

12.2.1 Biodegradation

- There is no data available for this product.
- **12.2.2** Chemical degradation There is no data available for this product.
- **12.3 Bioaccumulative potential** There is no data available for this product.
- **Mobility in soil**There is no data available for this product.
- 12.5 Results of PBT and vPvB assessment
- 12.6 Other adverse effects

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

- Do not burn, or use a cutting torch on, the empty drum. Dispose of in accordance with local regulations.
- **13.2** Waste from residues / unused products There is no data available for this product.

14.1 UN number

SAFETY	Page 6/6	
PRF Silicon		
Date 12.6	5.2017 Previous d	late: 15.11.2016
14.2	UN proper shipping name	Aerosols
14.3	Transport hazard class(es)	2.1
14.4	Packing group	-
14.5	Environmental hazards	Environmentally hazardous
14.6	Special precautions for users	
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	
15. REGULATORY INFORMATION		

- **15.1** Safety, health and environmental regulations/legislation specific for the substance or mixture 2B Aerosols
- 15.2 Chemical safety assessment

16. OTHER INFORMATION

- 16.1 Additions, Deletions, Revisions REGULATION (EC) No 453/2010
- **16.8** Additional information available from: tilaukset(at)taerosol.com