

Material: 60003765 ELASTOSIL® RT 607 A

Version: 2.3 (GB) Date of print: 06.03.2018 Date of last alteration: 22.06.2016

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial product name: ELASTOSIL® RT 607 A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / preparation:

Industrial.

Casting compound

1.3 Details of the supplier of the safety data sheet

Manufacturer/distributor: Wacker Chemie AG
Street/POB-No.: Hanns-Seidel-Platz 4
State/postal code/city: D 81737 München
Telephone: +49 89 6279-0
Telefax: +49 89 6279-1770

Information about the Safety Data Sheet: Telephone +49 8677 83-4888
Telefax +49 8677 886-9722

eMail WLCP-MSDS@wacker.com

1.4 Emergency telephone number

Emergency Information (German): Plant fire brigade +49 8677 83-2222 Emergency Information (internat.): National Response Center +49 621 60-43333

# **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008:

Not a hazardous substance or mixture.

### 2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008:

No labeling according to GHS required.

Special labelling instructions:

Safety data sheet available on request.

### 2.3 Other hazards

No data available.

# **SECTION 3: Composition/information on ingredients**

# 3.1 Substances

not applicable

## 3.2 Mixtures

# 3.2.1 Chemical characteristics

Polydimethylsiloxane with functional groups and auxiliaries for addition cross-linking

# 3.2.2 Hazardous ingredients

Type	CAS No.	EC-No. REACH no.	Material	Content %	Classification according to Regulation (EC) No. 1272/2008*	Comment
INHA	14808-60-7	238-878-4	Quartz	>50 - <60	STOT RE 1 by inhalation; H372	[1]

Page: 1/8



Material: 60003765 ELASTOSIL® RT 607 A

Version: 2.3 (GB) Date of print: 06.03.2018 Date of last alteration: 22.06.2016

Type: INHA: ingredient, VERU: impurity

[1] = Hazardous or environmentally harmful substance; [2] = substance with a Community workplace exposure limit; [3] = PBT substance; [4] = vPvB substance

\*Classification codes are explained in section 16.

Quartz: This component does not impact the product's hazard classification. Due to the product's physical properties, particulate inhalation exposure is not possible.

# SECTION 4: First aid measures

## 4.1 Description of first aid measures

#### **General information:**

In case of accident or if you feel unwell seek medical advice (show label or SDS where possible).

#### After contact with the eyes:

Rinse immediately with plenty of water. Seek medical advice in case of continuous irritation.

#### After contact with the skin:

Wash with plenty of water or water and soap. In the event of a visible skin change or other complaints, seek medical advice (show label or SDS where possible).

## After inhalation:

Provide fresh air.

#### After swallowing:

Give several small portions of water to drink. Do not induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

# 4.3 Indication of any immediate medical attention and special treatment needed

Further toxicology information in section 11 must be observed.

## **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

## Suitable extinguishing media:

water mist, extinguishing powder, alcohol-resistant foam, carbon dioxide, sand.

#### Extinguishing media which must not be used for safety reasons:

water jet .

## 5.2 Special hazards arising from the substance or mixture

Risk of hazardous gasses or fumes in the event of fire. Exposure to combustion products may be a health hazard! Hazardous combustion products: carbon oxides , silicon oxides , incompletely burnt hydrocarbons , toxic and very toxic fumes .

## 5.3 Advice for firefighters

## Special protective equipment for fire fighting:

Use respiratory protection independent of recirculated air. Keep unprotected persons away.

# SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. If material is released indicate risk of slipping. Do not walk through spilled material.

# 6.2 Environmental precautions

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

Page: 2/8



Material: 60003765 ELASTOSIL® RT 607 A

Version: 2.3 (GB) Date of print: 06.03.2018 Date of last alteration: 22.06.2016

# 6.3 Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

#### 6.4 Reference to other sections

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

# SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### **General information:**

Stir thoroughly before use or catalysing.

## Precautions for safe handling:

Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Spilled substance increases risk of slipping. Observe information in section 8.

### Precautions against fire and explosion:

Observe the general rules for fire prevention.

# 7.2 Conditions for safe storage, including any incompatibilities

# Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

### Advice for storage of incompatible materials:

Observe local/state/federal regulations.

# Further information for storage:

Store in a dry and cool place.

# 7.3 Specific end use(s)

No data available.

# SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

## Maximum airborne concentrations at the workplace:

not applicable

# 8.2 Exposure controls

### 8.2.1 Exposure in the work place limited and controlled

### General protection and hygiene measures:

Observe standard industrial hygiene practices for the handling of chemical substances. Do not eat or drink when handling.

### Personal protection equipment:

### Respiratory protection

No personal respiratory protective equipment normally required.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Suitable respiratory equipment: Filtering half-face mask, according to acknowledged standards such as EN 149.

Recommended Filter type: FFP1 or equivalent filter, according to acknowledged standards such as EN 149

Observe the equipment manufacturer's information and wear time limits for respirators.

## Eye protection

Recommendation: protective goggles .

Page: 3/8



Material: 60003765 **ELASTOSIL® RT 607 A** 

Version: 2.3 (GB) Date of print: 06.03.2018 Date of last alteration: 22.06.2016

## Hand protection

Use of protective gloves is recommended when handling the material.

Recommended glove types: Protective gloves made of nitrile rubber

thickness of the material: > 0,1 mm Breakthrough time: > 480 min

Recommended glove types: Protective gloves made of butyl rubber

thickness of the material: > 0,3 mm Breakthrough time: > 480 min

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Note that, due to the numerous external influences (such as temperature), a chemically resistant protective glove in daily use may have a service life that is considerably shorter than the measured break through time.

## 8.2.2 Exposure to the environment limited and controlled

Prevent material from entering surface waters, drains or sewers and soil.

# SECTION 9: Physical and chemical properties

Appearance	Property:	Value:	Method:
Colour         reddish brown           Odour         odourless           PH-Value         not applicable           Melting point/freezing point         Melting point / melting range           Melting point / boiling range         not applicable           Initial boiling point / boiling range         not applicable           Flash point         > 200 °C         (DIN 51376)           Upper/lower flammability or explosive limits         Lower explosion limit (LEL)         not applicable           Upper explosion limit (UEL)         not applicable           Vapour pressure         not applicable           Vapour pressure         not applicable           Solubility(les)         water solubility / miscibility           Water solubility / miscibility         virtually insoluble at 20 °C           Vapour density         No data known.           Relative Density         approx. 1,5         (DIN 51757)           Relative Density         approx. 1,5 g/cm³         (DIN 51757)           Partition coefficient: n-octanol/water         No data known.           Partition temperature         > 450 °C         (DIN 51794)           Decomposition temperature         > 450 °C         (DIN 51794)			
Odour         odourless           pH-Value         not applicable           Melting point/freezing point         Melting point / melting range           Melting point / boiling range         not applicable           Flash point         > 200 °C           Flash point         > 200 °C           Upper/lower flammability or explosive limits         not applicable           Lower explosion limit (LEL)         not applicable           Upper explosion limit (UEL)         not applicable           Vapour pressure         not applicable           Vapour pressure         not applicable           Solubility(es)         virtually insoluble at 20 °C           Vapour density         virtually insoluble at 20 °C           Vapour density         No data known.           Relative Density         approx. 1,5         (DIN 51757)           Relative Density         approx. 1,5         (DIN 51757)           Partition coefficient: n-octanol/water         not data known.           Partition coefficient: n-octanol/water         No data known.           Auto-ignition temperature         > 450 °C         (DIN 51794)           Decomposition temperature         > 200 °C           Thermal decomposition         > 200 °C	,	•	
Odour         odourless           pH-Value         pH-Value           pH-Value         not applicable           Melting point/freezing point         melting point point of melting range           Initial boiling point / boiling range         not applicable           Boiling point / boiling range         not applicable           Flash point         > 200 °C         (DIN 51376)           Upper/lower flammability or explosive limits         Lower explosion limit (LEL)         not applicable           Upper explosion limit (UEL)         not applicable           Vapour pressure         not applicable           Vapour pressure         not applicable           Solubility(ies)         virtually insoluble at 20 °C           Vapour density         virtually insoluble at 20 °C           Vapour density         No data known.           Relative Density         approx. 1,5         (DIN 51757)           Relative Density         approx. 1,5 g/cm³         (DIN 51757)           Partition coefficient: n-octanol/water         No data known.           Auto-ignition temperature         No data known.           Ignition temperature         > 450 °C         (DIN 51794)           Decomposition temperature         > 200 °C		reddish brown	
pH-Value pH-Value			
PH-Value		odourless	
Melting point/freezing point     Melting point / melting range     not applicable       Initial boiling point and boiling range     not applicable       Boiling point / boiling range     not applicable       Flash point     > 200 °C     (DIN 51376)       Upper/lower flammability or explosive limits     not applicable       Lower explosion limit (LEL)     not applicable       Upper explosion limit (UEL)     not applicable       Vapour pressure     not applicable       Vapour pressure     not applicable       Solubility(ies)     virtually insoluble at 20 °C       Vapour density     No data known.       Relative Density     approx. 1,5     (DIN 51757)       Relative Density     approx. 1,5 g/cm³     (DIN 51757)       Partition coefficient: n-octanol/water     No data known.       Partition coefficient: n-octanol/water     No data known.       Auto-ignition temperature     > 450 °C     (DIN 51794)       Decomposition temperature     > 450 °C     (DIN 51794)       Thermal decomposition     > 200 °C			
Melting point / melting range		not applicable	
Initial boiling point and boiling range Boiling point / boiling range			
Boiling point / boiling range		not applicable	
Flash point Flash point Flash point Flash point Flash point Solupper/lower flammability or explosive limits Lower explosion limit (LEL) Upper explosion limit (UEL) Inot applicable Vapour pressure Vapour pressure Vapour pressure Vapour pressure Vapour density Relative gas/vapour density Relative Density Relative Density Relative Density No data known Relative Density Relative Density No data known No data known Relative Density No data known	· · · · · · · · · · · · · · · · · · ·		
Flash point	51 5 5	not applicable	
Upper/lower flammability or explosive limits  Lower explosion limit (LEL)	·		
Lower explosion limit (LEL)		> 200 °C	(DIN 51376)
Upper explosion limit (UEL)	Jpper/lower flammability or explosive limits		
Vapour pressure not applicable   Solubility(ies) virtually insoluble at 20 °C   Vapour density virtually insoluble at 20 °C   Relative gas/vapour density No data known.   Relative Density approx. 1,5 (Water / 4 °C = 1,00)   Density approx. 1,5 g/cm³   Partition coefficient: n-octanol/water No data known.   Partition coefficient: n-octanol/water No data known.   Auto-ignition temperature Ignition temperature   Ignition temperature > 450 °C   Decomposition temperature > 200 °C   Viscosity			
Vapour pressure	• • • • • • • • • • • • • • • • • • • •	not applicable	
Solubility(ies) Water solubility / miscibility	• •		
Water solubility / miscibility		not applicable	
Vapour density Relative gas/vapour density No data known.   Relative Density approx. 1,5 (Water / 4 °C = 1,00) (DIN 51757)   Density approx. 1,5 g/cm³ (DIN 51757)   Partition coefficient: n-octanol/water No data known.   Partition temperature No data known.   Ignition temperature > 450 °C (DIN 51794)   Decomposition temperature > 200 °C   Viscosity			
Relative gas/vapour density		virtually insoluble at 20 °C	
Relative Density Relative Density	1		
Relative Density		No data known.	
Density			
Density	Relative Density:	approx. 1,5	(DIN 51757)
Partition coefficient: n-octanol/water Partition coefficient: n-octanol/water			
Partition coefficient: n-octanol/water	Density:	approx. 1,5 g/cm <sup>3</sup>	(DIN 51757)
Auto-ignition temperature   Ignition temperature	Partition coefficient: n-octanol/water		
Ignition temperature	Partition coefficient: n-octanol/water:	No data known.	
Decomposition temperature Thermal decomposition			
Thermal decomposition > 200 °C  Viscosity	Ignition temperature:	> 450 °C	(DIN 51794)
Viscosity			
	Thermal decomposition:	> 200 °C	
Viscosity (dynamic) 15000 mPa.s			

9.2

No data available.



Material: 60003765 ELASTOSIL® RT 607 A

Version: 2.3 (GB) Date of print: 06.03.2018 Date of last alteration: 22.06.2016

# **SECTION 10: Stability and reactivity**

## 10.1 - 10.3 Reactivity; Chemical stability; Possibility of hazardous reactions

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

Relevant information can possibly be found in other parts of this section.

### 10.4 Conditions to avoid

none known

### 10.5 Incompatible materials

none known

### 10.6 Hazardous decomposition products

If stored and handled properly: none known . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150  $^{\circ}$ C (302  $^{\circ}$ F) through oxidation.

# **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

# 11.1.1 Acute toxicity

#### **Assessment:**

For this endpoint no toxicological test data is available for the whole product.

### Acute toxicity estimate (ATE):

 $ATE_{mix}$  (oral): > 2000 mg/kg

# 11.1.2 Skin corrosion/irritation

### Assessment:

For this endpoint no toxicological test data is available for the whole product.

# 11.1.3 Serious eye damage / eye irritation

### Assessment:

For this endpoint no toxicological test data is available for the whole product.

### 11.1.4 Respiratory or skin sensitization

#### Assessment:

For this endpoint no toxicological test data is available for the whole product.

### 11.1.5 Germ cell mutagenicity

#### Assessment:

For this endpoint no toxicological test data is available for the whole product.

# 11.1.6 Carcinogenicity

### **Assessment:**

For this endpoint no toxicological test data is available for the whole product.

### 11.1.7 Reproductive toxicity

#### Assessment:

For this endpoint no toxicological test data is available for the whole product.

# 11.1.8 Specific target organ toxicity (single exposure)

#### Assessment:

For this endpoint no toxicological test data is available for the whole product.

Page: 5/8



Material: 60003765 ELASTOSIL® RT 607 A

Version: 2.3 (GB) Date of print: 06.03.2018 Date of last alteration: 22.06.2016

### 11.1.9 Specific target organ toxicity (repeated exposure)

#### Assessment:

For this endpoint no toxicological test data is available for the whole product.

## 11.1.10 Aspiration hazard

#### Assessment:

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

# **SECTION 12: Ecological information**

### 12.1 Toxicity

#### Assessment:

For the product as a whole, no test data is available. According to current knowledge adverse effects on water purification plants are not expected.

# 12.2 Persistence and degradability

#### Assessment:

Silicone content: biologically not degradable. Separation by sedimentation.

### 12.3 Bioaccumulative potential

#### Assessment:

No adverse effects expected.

### 12.4 Mobility in soil

### **Assessment:**

For the product as a whole, no test data is available.

### 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

none known

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

# 13.1.1 Material

# Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

# 13.1.2 Uncleaned packaging

# Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

# 13.1.3 Waste Disposal Legislation Ref.No.(EC)

It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Page: 6/8



Material: 60003765 ELASTOSIL® RT 607 A

Version: 2.3 (GB) Date of print: 06.03.2018 Date of last alteration: 22.06.2016

# **SECTION 14: Transport information**

### 14.1 – 14.4 UN number; UN proper shipping name; Transport hazard class(es); Packing group

Road ADR:

Valuation ...... Not regulated for transport

Railway RID:

Valuation ...... Not regulated for transport

**Transport by sea IMDG-Code:** 

Valuation ...... Not regulated for transport

Air transport ICAO-TI/IATA-DGR:

Valuation ...... Not regulated for transport

14.5 Environmental hazards

Hazardous to the environment: no

14.6 Special precautions for user

Relevant information in other sections has to be considered.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk transport in tankers is not intended.

# SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National and local regulations must be observed.

For information on labelling please refer to section 2 of this document.

Relevant regulations:

SI 2002/1689: CHIP Regulations 2002 SI 2002/2677: COSHH Regulations 2002

SI 1999/3242: Management of Health & Safety at Work Regulations 1999

Health & Safety at Work Act 1974

SI 1993/1643: Environmental Protection Act 1993 & Subsidiary Regulations.

Other national and local measures relating to the workplace, pollution control, environmental protection and waste control.

### 15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

## 15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

South Korea (Republic of Korea) .....: ECL (Existing Chemicals List):

This product is listed in, or complies with, the substance inventory.

This product is listed in, or compiles with, the substance inventory

People's Republic of China .....: IECSC (Inventory of Existing Chemical Substances in China):

This product is listed in, or complies with, the substance inventory.

Canada ...... DSL (Domestic Substance List):

This product is listed in, or complies with, the substance inventory.

Philippines : PICCS (Philippine Inventory of Chemicals and Chemical Substances): This product is listed in, or complies with, the substance inventory.

United States of America (USA)...... TSCA (Toxic Substance Control Act Chemical Substance Inventory):

This product is listed in, or complies with, the substance inventory.

Page: 7/8



Material: 60003765 **ELASTOSIL® RT 607 A** 

Version: 2.3 (GB) Date of print: 06.03.2018 Date of last alteration: 22.06.2016

European Economic Area (EEA)...... REACH (Regulation (EC) No 1907/2006):

General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.

## **SECTION 16: Other information**

#### 16.1 Material

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product. This applies in particular to the further sale or distribution of the product or substances or items containing the product, in other jurisdictions and with regard to the protection of third-party intellectual property rights. If the described product is processed or mixed with other substances or materials, the details stated in this document cannot be conferred to the resultant new product unless this has been expressly mentioned. If the product is repackaged, the recipient is obligated to additionally provide the required safety-related information.

All deliveries are subject to the WACKER SILICONES Health Care Policy, which is available at www.wacker.com.

#### 16.2 Further information:

Commas appearing in numerical data denote a decimal point. Vertical lines in the left-hand margin indicate changes compared with the previous version. This version supersedes all previous versions.

Explanation of the GHS classification code:

STOT RE 1; H372 ...... Specific target organ toxicity (repeated exposure) Category 1; Causes damage to organs through prolonged or repeated exposure.

- End of Safety Data Sheet -

Page: 8/8