Pliers & Cutters (Swiss Made)



1. Features

- High quality ball bearing steel
- 63 65 Rockwell Hardness (HRC): Pyrometer controlled inductive hardening
- All cutters available with three types of cutting blades:
 - o **SEMI-FLUSH**, for soft and hard wire.
 - o **FLUSH**, for very precise cutting of soft wire.
 - o **FULL-FLUSH**, for a perfect cutting of soft wire.



- 2-Component ESD Ergonomic handles, soft comfortable gripping surface, hard plastic core
- Dual leaf springs in blue steal.
- Matched bearing rings in order to minimize metal-metal contact and friction.
- Lap joint with screw in order to achieve a high level of strength and precision. The nut is made of hardened alloy steel in order to resist high cutting load. The screw is fine-pitched for perfect joint adjustment.

2. The cutters


Oval

<u>Micro</u>: very slim, relieved to maximize accessibility when limited space <u>Small</u>: robust, slim shape, an optimum balance between durability and accessibility.

Big: very strong and durable, for intensive cutting operations.

| | | | I - | | | | |
|---------|------|------|------|------|------|------------|------------------|
| Product | Α | В | С | D | F | Cutting | Cutting capacity |
| Code | [mm] | [mm] | [mm] | [mm] | [mm] | edges | Cu-wire [mm] |
| 5130 | 121 | 8 | 8 | 6.4 | 0.5 | Semi-flush | 0.2-1.2 |
| 5131 | 121 | 8 | 8 | 6.4 | 0.5 | Flush | 0.1-1.2 |
| 5132 | 121 | 8 | 8 | 6.4 | 0.5 | Full-flush | 0.1-0.8 |
| 5140 | 123 | 10 | 10 | 6.4 | 0.5 | Semi-flush | 0.2-1.2 |
| 5141 | 123 | 10 | 10 | 6.4 | 0.5 | Flush | 0.1-1.2 |
| 5142 | 123 | 10 | 10 | 6.4 | 0.5 | Full-flush | 0.1-1.0 |
| 5150 | 125 | 12.5 | 12.5 | 6.4 | 0.5 | Semi-flush | 0.3-1.6 |
| 5151 | 125 | 12.5 | 12.5 | 6.4 | 0.5 | Flush | 0.2-1.6 |
| 5152 | 125 | 12.5 | 12.5 | 6.4 | 0.5 | Full-flush | 0.2-1.2 |






Tapered


Micro: pointed head shape, very slim, relieved to maximize accessibility when limited space

<u>Small</u>: pointed head shape, slim an optimum balance between durability and accessibility.

<u>Big</u>: Robust and versatile. Pointed head shape to increase accessibility when limited space.

| Product | Α | В | С | D | F | Cutting | Cutting capacity |
|---------|------|------|------|------|------|------------|------------------|
| Code | [mm] | [mm] | [mm] | [mm] | [mm] | edges | Cu-wire [mm] |
| 5330 | 121 | 8 | 8 | 6.4 | 0.5 | Semi-flush | 0.2-1.2 |
| 5331 | 121 | 8 | 8 | 6.4 | 0.5 | Flush | 0.1-1.2 |
| 5332 | 121 | 8 | 8 | 6.4 | 0.5 | Full-flush | 0.1-0.8 |
| 5340 | 123 | 10 | 10 | 6.4 | 0.5 | Semi-flush | 0.2-1.2 |
| 5341 | 123 | 10 | 10 | 6.4 | 0.5 | Flush | 0.1-1.2 |
| 5342 | 123 | 10 | 10 | 6.4 | 0.5 | Full-flush | 0.1-1.0 |
| 5350 | 125 | 12.5 | 12.5 | 6.4 | 0.5 | Semi-flush | 0.3-1.6 |
| 5351 | 125 | 12.5 | 12.5 | 6.4 | 0.5 | Flush | 0.2-1.6 |
| 5352 | 125 | 12.5 | 12.5 | 6.4 | 0.5 | Full-flush | 0.2-1.2 |







• Tapered and relieved

Pointed head shape and deep relief for a very low profile to maximize accessibility when limited space.

| Product Code | A [mm] | B [mm] | C [mm] | D [mm] | F [mm] | Cutting edges | Cutting capacity Cu-wire [mm] |
|-----------------|-----------|-----------|-----------|-----------|-----------|------------------|----------------------------------|
| 5540 | 123 | 10 | 10 | 6.4 | 0.5 | Semi-flush | 0.2-1.2 |
| 5541 | 123 | 10 | 10 | 6.4 | 0.5 | Flush | 0.1-1.2 |
| 5542 | 123 | 10 | 10 | 6.4 | 0.5 | Full-flush | 0.1-1.0 |






3. The Pliers

• Snipe nose long

Commonly used in electronic assembly and rework as well as in fine jewellery and beading work. Pliers nose have flat-faced inner jaws.

| Product | Α | В | С | D | E | F | Jaw |
|---------|------|------|------|------|------|------|----------|
| Code | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | shape |
| 6023 | 143 | 30 | 10 | 6.4 | 1.2 | 1.0 | smooth |
| 6024 | 143 | 30 | 10 | 6.4 | 1.2 | 1.0 | serrated |






• Snipe nose

Commonly used in electronic assembly and rework as well as in fine jewellery and beading work. Long bent nose pliers have flat-faced inner jaws.

| Product | Α | В | С | D | E | F | Jaw |
|---------|------|------|------|------|------|------|----------|
| Code | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | shape |
| 6021 | 133 | 20 | 10 | 6.4 | 1.2 | 1.0 | smooth |
| 6022 | 133 | 20 | 10 | 6.4 | 1.2 | 1.0 | serrated |






Flat nose

Flat nose pliers feature a very fine tip, smooth jaws and inner edges.

| Product | Α | В | С | D | Е | F | Jaw |
|---------|------|------|------|------|------|------|--------|
| Code | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | shape |
| 6011 | 133 | 20 | 10 | 6.4 | 1.2 | 4.0 | smooth |






Round nose

Round nose pliers have jaws formed by two long cones. A round nose pliers is generally used both to clamp and to form loops on leads or wire. The long jaws also provide increased access.

| Product | Α | В | С | D | E | F | Jaw |
|---------|------|------|------|------|------|-------|-----------|
| Code | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | shape |
| 6041 | 133 | 20 | 10 | 6.4 | 2.0 | Ø 1.0 | Very fine |





Commonly used in electronic assembly and rework as well as in fine jewellery and beading work. Pliers nose have flat-faced inner jaws.

The thin profile increases tool access. The cone shape can be used for precision loop forming of leads or wire. Needle nose pliers feature very fine tips. Also the inner edges of the jaw are "eased" to protect leads or wire during forming.

| Product | Α | В | С | D | E | F | Jaw |
|---------|------|------|------|------|------|------|--------|
| Code | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | shape |
| 6025 | 146 | 33 | 10 | 6.4 | 1.2 | 0.8 | smooth |



