Inventec Performance Chemicals USA, LLC SAFETY DATA SHEET (SDS)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:	Lead Free (LF) alloyed products containing Antimony, Bismuth, Copper, Gold, Nickel, Silver, and Tin
BRANDS:	Amtech, Gesick MPM
SYNONYMS:	LF Powder, LF Spheres, LF Preforms, LF Bar Solder, LF Solid Wire
MANUFACTURER:	Inventec Performance Chemicals USA, LLC
ADDRESS:	PO Box 989 Deep River, CT 06417 USA
PHONE:	860-526-8300
FAX:	860-526-8243
EMERGENCY:	Infotrac-(800)535-5035
REVISION DATE:	December 19, 2014
REVISION NUMBER:	2
DOCUMENT NAME:	SDS-Alloys-010
PRODUCT USE:	Soldering components for bonding semiconductor chips and packages to circuit boards

SECTION 2: HAZARDS IDENTIFICATION

CHEMICAL NAME:	N/A
CHEMICAL FAMILY:	Inorganic Metals
CHEMICAL FORMULA:	N/A

ROUTES OF ENTRY: Inhalation, Ingestion, Skin/Eye Contact



Signal Word: Warning

Hazard statement(s)

H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H333	May be harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

Precautionary statement(s)

Keep out of reach of children
Avoid breathing dust/fume/gas/mist/vapors/spray
Do not eat, drink, or smoke when using this product
Wear protective gloves/protective eye protection/face protection
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
IF ON SKIN: Wash with plenty of soap and water
IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing
IF IN EYES: Rinse continuously with water for several minutes

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE:

Diseases of the blood-forming organs, kidneys, nervous and possibly reproductive systems

POTENTIAL HEALTH EFFECTS

- **EYE CONTACT:** May cause moderate irritation, tearing, and reddening. Contact with fumes from molten metal may cause irritation.
- **INHALATION:** Inhalation of fumes or dust may cause local irritation to the respiratory system, dizziness, weakness, fatigue, nausea, and/or headache.
- SKIN CONTACT: May cause mild skin irritation.

INGESTION: Harmful if swallowed. May cause irritation to the mouth, throat, and stomach. May cause abdominal discomfort, nausea, vomiting, and/or diarrhea.

POTENTIAL HEALTH EFFECTS (CHRONIC & OVEREXPOSURE)

- TIN: Dust or fumes may cause irritation of the skin mucous membranes and may result in a benign Pneumoconiosis (Stannosis).
- SILVER: May cause discoloration of eyes and skin (Argyia).
- BISMUTH: May cause foul breath, a blue-black line on the gums, and Stomatitis.

Page 1 of 4 SDS-Alloys-010

SECTION 2: HAZARDS IDENTIFICATION (continued)

ANTIMONY: May cause gastrointestinal upset, sleeplessness, irritability, and muscular pain.

SECTION 2 NOTES:

Inventec Performance Chemicals USA, LLC does not recommend, manufacture, market, or endorse any of its products for human consumption.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS			
Ingredie	nt <u>CAS Number</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Tin	7440-31-5	2.0 MG/M ³	2.0 MG/M ³
Silver	7440-22-4	0.01 MG/M ³	0.1 MG/M ³
Bismuth	7440-69-9	Not Established	Not Established
Antimon	y 7440-36-0	0.5 MG/M ³	0.5 MG/M ³
Nickel	7440-02-0	1.0 Mg./Cu. M.	1.0 Mg./Cu. M.
Copper	7440-50-8	1.0 Mg./Cu. M.	1.0 Mg./Cu. M.
Gold	7440-57-5	Not Established	Not Established

SECTION 3 NOTES:

Product contains one or more of these metallic elements in varying percentages.

SECTION 4: FIRST AID MEASURES

EYES: Flush with water, contact a physician. Dust and/or fumes may cause irritation. If contact lenses can be removed easily, flush eyes without contact lenses.

SKIN: For hot metal burns, exposed area should be cooled with water and medical attention sought. After handling material wash hands thoroughly with soap and water. Dust, vapor, and/or fumes are not readily absorbed through the skin.

INGESTION: Call a physician or Poison Control Center immediately. Do not induce vomiting.

INHALATION: If symptoms are present, the individual should be immediately removed from exposure and a physician consulted.

SECTION 5: FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Use extinguishers appropriate for conditions.

SPECIAL FIRE FIGHTING PROCEDURES: Use NIOSH-approved self-contained Breathing Apparatus and full protective clothing if involved in a fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Moderate in the form of dust when exposed to heat or flame.

SECTION 5 NOTES:

Molten solder alloys consisting of Antimony, Bismuth, Copper, Gold, Silver, and/or Tin do not produce significant quantities of fumes below 900 °F.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Material is non-hazardous. Follow directions listed under HANDLING/STORAGE.

SECTION 6 NOTES:

See Sections 2, 4, and 7 for additional information.

SECTION 7: HANDLING AND STORAGE

HANDLING/STORAGE: Avoid inhalation of solder fumes or dust. Vacuuming is recommended. Do not use dry sweeping or compressed air cleaning systems. Wear protective gloves to pick up solid metal pieces. Dispose of following Federal, State/Provincial, and Local regulations. Metal may have reclaim value.

WORK HYGIENIC PRACTICES: Cosmetics/Food/Drink/Tobacco should not be consumed or used in areas where solder products may be used. Always wash hands after handling soldering products and before applying or using cosmetics/food/drink/tobacco.

OTHER PRECAUTIONS: Empty containers may retain product residues in vapor, liquid, and/or solid form. All labeled hazard precautions must be observed.

SECTION 7 NOTES:

For industrial use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLVs.

RESPIRATORY PROTECTION: A NIOSH-approved dust/fume respirator should be worn when applicable limits may be exceeded.



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

EYE PROTECTION: Safety glasses and/or face protection is recommended for exposures where there is a risk of dust or hot metal splashing.

SKIN PROTECTION: Protective gloves should be worn to reduce burn exposure. Disposable gloves are recommended to minimize direct exposure to material.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: SHAPE: ODOR: ODOR THRESHOLD: pH as SUPPLIED: MELTING POINT: FREEZING POINT: INITIAL BOILING POINT: BOILING RANGE: FLASH POINT: EVAPORATION RATE: FLAMMABILITY (solid): UPPER/LOWER FLAMMABILITY: UPPER/LOWER FLAMMABILITY: UPPER/LOWER FLAMMABILITY: UPPER/LOWER EXPLOSIVE LIMITS: VAPOR PRESSURE (mmHg): VAPOR DENSITY (AIR = 1): RELATIVE DENSITY: SOLUBILITY IN WATER: PARTITION COEFFICIENT (n-octanol/water): AUTOIGNITION TEMPERATURE: DECOMPOSITION TEMPERATURE: VISCOSITY:	Silver-gray Sphere, rectangular, or washer shaped; wire; bar or ingot form Odorless Not established N/A Varies Varies Varies Varies N/A (°F/°C) N/A Not established Not established Not established N/A (°F/°C) N/A (°F/°C) Not established Insoluble Not established Not established
SECTION 9 NOTES: Some typical alloy compositions 96.5%Tin/3%Silver/0.5	
95%Tin/5%Antimony 42%Tin/58%Bismuth	95.5% Tin/4.0% Silver/0.5% Copper 80% Gold/20% Tin
SECTION 10: STABILITY AND REACTIVITY	
STABILITY: CONDITIONS TO AVOID (STABILITY): INCOMPATIBILITY (MATERIAL TO AVOID): HAZARDOUS DECOMPOSITION/BY-PRODUCTS: POSSIBILITY OF HAZARDOUS REACTIONS: SECTION 11: TOXICOLOGICAL INFORMATION	Stable Not established Oxidizing materials, acids, hydrogen peroxide N/A Will not occur
ACUTE TOXICITY:	
Antimony (7440-36-0) LD50 Ingested rat	7000 mg/kg
	rooo marka
Silver (7440-22-4)	
LD50 Oral mouse	100/mg/kg
SERIOUS EYE DAMAGE/IRRITATION:NoRESPIRATORY OR SKIN SENSITIZATION:NoGERM CELL MUTAGENICITY:NoCARCINOGENICITY:NoREPRODUCTIVE TOXICITY:NoSTOT-SINGLE EXPOSURE:NoSTOT-REPEATED EXPOSURE:No	t established t available t established t available t available t available t available t available t available
SECTION 12: ECOLOGICAL INFORMATION	
PERSISTENCE AND DEGRADABILITY: No BIOACCUMULATIVE POTENTIAL: No	t established t established t established t established
	Page 3 of 4 SDS-Alloys-010

SECTION 12: ECOLOGICAL INFORMATION (continued)

OTHER ADVERSE EFFECTS:

Not established

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Scrap and waste solder should be recycled or stored in a dry, sealed container for later disposal. Disposal must be in accordance with standards, regulations, laws, and statutes set forth by Federal, State/Provincial, and Local Regulations.

SECTION 14: TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.

UN Number: UN Proper Shipping Name: Packaging Group: Environmental Hazards:	Not available Not available Not applicable None
TRANSPORT HAZARD CLASSES: US DOT Hazardous Material Classification: Water Transportation: IATA Hazardous Material Classification:	Alloyed Products are not listed as a DOT hazardous material Alloyed Products are not listed as a hazardous material Alloyed Products are not listed as IATA hazardous material
SECTION 15: REGULATORY INFORMATION All ingredients are listed on the EPA TSCA Inventory. Fi	nished product is not listed on the EDA TSCA lowentery

U.S. FEDERAL REGULATIONS: STATE REGULATIONS: INTERNATIONAL REGULATIONS:	None None None	

Flammability=1

SECTION 16: OTHER INFORMATION

HMIS Rating: Health=1

Physical Hazard=0

Personal Protection=X

PREPARATION INFORMATION:

This update supersedes all previously released documents.

KEY:	
N/A:	Not applicable
GHS:	Global Harmonized System
CAS:	Chemical Abstract Service
OSHA:	Occupational Safety and Health Administration
PEL:	Permissible Exposure Limit
ACGIH:	American Conference of Governmental Industrial Hygienists
LD50:	Lethal Dose, 50% or medial lethal dose
STOT:	Specific target organ toxicity
TLV:	Threshold limit value
NTP:	National Toxicology Program
IARC:	International Agency for Research on Cancer
NIOSH:	National Institute for Occupational Safety and Health
US DOT:	United States Department of Transportation
DOT:	Department of Transportation
IATA:	International Air Transport Association
EPA:	Environmental Protection Agency
TSCA:	Toxic Substance Control Act
HMIS:	Hazardous Material Identification System

PREPARED BY: Wendy W. Gesick **APPROVED BY:** Leigh W. Gesick

DISCLAIMER:

The information contained herein is based on data considered to be accurate but does not purport to be all-inclusive and shall be used only as a guide. No warranty is expressed or implied regarding the accuracy of this data and Inventec Performance Chemicals USA, LLC shall not be held liable for any damage resulting from any handling or contact with the above product. Liability is expressly disclaimed for loss or injury arising out of use of this information or the use of any materials designated.

This material is not for resale, unauthorized distribution, or personal use.