



Label printer | thermal transfer | max. 104 mm

Product code: 50244

The thermal transfer label printer, thanks to its performance, is ideally suited for use in office environments, storage systems and logistics.

TECHNICAL DATA

PRINTING METHOD	Thermal transfer
RESOLUTION	203 dpi
PRINTING WIDTH	Max. 104 mm
PAPER WIDTH	20 mm - 150 mm
PRINTING SPEED	127 mm/s
MEMORY	4 MB
INTERFACE	USB, Ethernet, Serial, Parallel
PRINTING BARCODES	Code39, Code93, Code128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-13, EAN-14, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POS, ITF14
GRAPHICS	Support BMP/PCX/BAS
PAPER TYPE	Continuous paper, gap paper, fold paper, black label paper
INPUT POWER SUPPLY	24V / 2.5A
PAPER THICKNESS	0.058 mm - 0.305 mm
USAGE	Industry and commerce, printing receipts, bills, prescriptions, invoices or tickets, etc.
WEIGHT	2.35 kg
DIMENSIONS	223 x 286 x 169 mm
OPERATING TEMPERATURE	5 C to +45 C

STORAGE TEMPERATURES

-10 C to +50 C

HUMIDITY

Operating: 25% - 85%, Storage: 10% - 90%

EAN CODE

5901878502441