


# SPECIFICATION FOR APPROVAL

COMMODITY	PK CHOKE		SPEC NO.	SP-060824035
ITEM	COIL0406-0.047	Green	B	TRR-002

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
 <p>UL TUBE</p>	A	5.5	MAX.
	B	7.5	MAX.
	C	16.0	±3.0
	D	0.5	±0.1
	E	2.0	±0.5
	F	3.0	MAX.
	G		
	H		
	I		
	J		

(2) ELECTRICAL CHARACTERISTIC			TEST INSTRUMENTS.
INDUCTANCE	47± 10%	μH	<input checked="" type="checkbox"/> AGILENT 4294A Precision Impedance Analyzer. <input type="checkbox"/> AGILENT 4285A Precision L.C.R. Meter. <input type="checkbox"/> HP-4286A RF L.C.R. Meter.
TEST FREQUENCY	1	kHz	<input type="checkbox"/> ZENTECH 3302 Automatic Components Analyzer. <input type="checkbox"/> ZENTECH 101 L.C.R. Meter.
TEST VOLT	0.25	V	<input type="checkbox"/> WAYNE KERR 6420 Precision Impedance Analyzer. <input checked="" type="checkbox"/> ZENTECH 1320 BIAS CURRENT.
RDC	0.376 (max)	Ω	<input checked="" type="checkbox"/> ZENTECH 502AC Resistance Meter. <input type="checkbox"/> ADEX AX-1155B DC Low Ohm Meter.
Isat	0.7 (max)	A	
Irms	0.9 (max)	A	

**REMARK :**

1. Inductance drop = 10% typ at Isat.
2. ΔT = 40°C rise typ at Irms.

# SPECIFICATION FOR APPROVAL

COMMODITY	PK CHOKE		SPEC NO.	SP-060824035
ITEM	COIL0406-0.047	Green	B	TRR-002
<b>(3) Material List</b>				
NO	ITEM	MATERIAL	NOTE	
1	CORE	Y2B DRWW 4*6F (B2 F3 P2)		
2	WIRE	2UEW 130°C CLASS 0.19/51Ts	155°C CLASS	
3	SOLDER	Sn 99.3 % / Cu 0.7%		
4	TUBE	UL4*7.2mm		