
















< List of part numbers with package codes > $LQM21NNR10K10D \ \ , \ LQM21NNR10K10J \ \ , \ LQM21NNR10K10B$

Shape



References

Packaging code	Specifications	Minimum quantity
D	ϕ 180mm Paper taping	4000
J	φ 330mm Paper taping	10000
В	Packing in bulk	1000

Mass (Typ.)	
1 piece	0.010g

Specifications

Inductance	0.10μH ±10%
Inductance test frequency	25MHz
Rated current (Isat) (Based on Inductance change)	250mA
Rated current (Itemp) (Based on Temperature rise)	250mA
Max. of DC resistance	0.26Ω
Q (min.)	20
Q test frequency	25MHz
Self resonance frequency (min.)	340MHz
Operating temperature range (Self-temperature rise is not included)	-40∼85℃
Class of magnetic shield	Magnetic shield of ferrite

1 of 2



^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




^{2.} This datasheet has only typical specifications because there is no space for detailed specifications.

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)

Inductance-Current characteristics (Typ.)



Q-Frequency characteristics (Typ.)



2 of 2



1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.