

KEMET Part Number: ALC80A221BB250
(A547CD221M250A)

ALC80, Aluminum Electrolytic, 220 uF, 20%, 250 VDC, -40/+105°C



Dimensions

Dimension	Value
D	25mm +1mm
L	30mm +/-2mm
S	10mm +/-0.1mm
LL	6.3mm +/-1mm
F	2mm +/-0.1mm

Packaging Specifications

Weight:	28 g
Packaging:	Bulk, Bag

General Information

Series:	ALC80
Dielectric:	Aluminum Electrolytic
Description:	Snap-In, Aluminum Electrolytic
RoHS:	Yes
Lead:	2 Pin
AEC-Q200:	No
Shelf Life:	156 Weeks

Specifications

Capacitance:	220 uF
Capacitance Tolerance:	20%
Voltage DC:	250 VDC, 288 VDC (Surge)
Temperature Range:	-40/+105°C
Rated Temperature:	105°C
Life:	6000 Hrs (Rated Voltage And Ripple Current At 105C), 10000 Hrs (Rated Voltage At 105C)
Resistance:	796 mOhms (100Hz 20C), 469 mOhms (10kHz 20C)
Ripple Current:	1.17 Amps (100Hz 105C), 2.7 Amps (10kHz 105C)
Leakage Current:	165 uA (5min 20°C)