

# KEMET Part Number: C0402C132J8JACTU

(C0402C132J8JAC7867, C0402C132J8JACTR, 0402C132J8JACTU)



Ceramic, Commercial Grade, KEMET, Commercial-(CxxxxC), 1300 pF, 5%, 10 V, 0402, U2J, SMD, MLCC, Ultra-Stable, Low Loss, Class I



## Dimensions

L	1mm +/-0.05mm
W	0.5mm +/-0.05mm
T	0.5mm +/-0.05mm
S	0.3mm MIN
B	0.3mm +/-0.1mm

## Packaging Specifications

Packaging:	T&R, 180mm, Paper Tape
Packaging Quantity:	10000

## General Information

Style:	SMD Chip
Manufacturer:	KEMET
Series:	Commercial-(CxxxxC)
Chip Size:	0402
Description:	SMD, MLCC, Ultra-Stable, Low Loss, Class I
Features:	Ultra-Stable, Low Loss, Class I
RoHS:	Yes
Termination:	Tin
Marking:	No
Failure Rate:	N/A
Miscellaneous:	Note: Referee time for U2J dielectric for this part number is 1000 hours

## Specifications

Capacitance:	1300 pF
Capacitance Tolerance:	5%
Voltage DC:	10 VDC
Temperature Range:	-55/+125C
Temperature Coefficient:	U2J
Dissipation Factor:	0.1%
Aging Rate:	0.1% Loss/Decade Hour
Dielectric Strength:	25 V

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006 - 2016 IntelliData.net