

**KEMET Part Number: C1210C107M9PACTU**  
(C1210C107M9PAC7800, C1210C107M9PACTR)

Ceramic, KEMET, Commercial-(CxxxxC), 100 uF, 20%, 6.3 V, 1210, X5R, SMD, MLCC, Temperature Stable, Class II



**Dimensions**

|          |                     |
|----------|---------------------|
| <b>L</b> | 3.2mm +/-0.3mm      |
| <b>W</b> | 2.5mm +/-0.3mm      |
| <b>T</b> | 2.5mm +/-0.30mm     |
| <b>B</b> | 0.5mm +0.35/-0.25mm |

**Packaging Specifications**

|                            |                          |
|----------------------------|--------------------------|
| <b>Packaging:</b>          | T&R, 180mm, Plastic Tape |
| <b>Packaging Quantity:</b> | 1000                     |

**General Information**

|                       |  |
|-----------------------|--|
| <b>Style:</b>         | SMD Chip   |
| <b>Supplier:</b>      | KEMET  |
| <b>Series:</b>        | Commercial-(CxxxxC)  |
| <b>Chip Size:</b>     | 1210   |
| <b>Description:</b>   | SMD, MLCC, Temperature Stable, Class II                                |
| <b>RoHS:</b>          | Yes  |
| <b>Termination:</b>   | Tin  |
| <b>Marking:</b>       | No   |
| <b>Failure Rate:</b>  | N/A  |
| <b>Miscellaneous:</b> | Note: Referee time for X5R dielectric for this part number is 48 hours |

**Specifications**

|                                 |                     |
|---------------------------------|---------------------|
| <b>Capacitance:</b>             | 100 uF              |
| <b>Capacitance Tolerance:</b>   | 20%                 |
| <b>Voltage DC:</b>              | 6.3 VDC             |
| <b>Temperature Range:</b>       | -55/+85C            |
| <b>Temperature Coefficient:</b> | X5R                 |
| <b>Dissipation Factor:</b>      | 10%                 |
| <b>Aging Rate:</b>              | 4% Loss/Decade Hour |
| <b>Insulation Resistance:</b>   | 1 MOhms             |
| <b>Dielectric Strength:</b>     | 15.75 V             |