
KEMET Part Number: C2824H393JBGACTU

(C2824H393JBGAC7800, C2824H393JBGACTR)



Ceramic, 200C, KEMET, 200C-(CxxxxH), 0.039 uF, 5%, 630 V, 2824, C0G, SMD, MLCC, High Temp, Ultra-Stable, Low Loss



General Information	
Style:	SMD Chip
Supplier:	KEMET
Series:	200C-(CxxxxH)
Chip Size:	2824
Description:	SMD, MLCC, High Temp, Ultra- Stable, Low Loss
RoHS:	Yes
Termination:	Tin
Marking:	No
Failure Rate:	N/A

Dimensions	
L	7.1mm +/-0.4mm
W	6.1mm +/-0.4mm
Т	2.5mm +/-0.20mm
В	0.76mm +/-0.4mm

Packaging Specifications	
Packaging:	T&R, 180mm, Plastic Tape
Packaging Quantity:	300

Specifications	
Capacitance:	0.039 uF
Capacitance Tolerance:	5%
Voltage DC:	630 VDC
Temperature Range:	-55/+200C
Temperature Coefficient:	COG
Dissipation Factor:	0.1%
Aging Rate:	0% Loss/Decade Hour
Insulation Resistance:	25.641 GOhms
Dielectric Strength:	945 V

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

