
KEMET Part Number: C921U222MUVDBAWL35



C900AH SFTY X1-400 Y1-250, Ceramic, 2200 pF, 20%, 400 VAC (X1), 250 VAC (Y1), Y5V, Lead Spacing = 10mm



Dimensions		
D	9mm MAX	
т	5.5mm MAX	
S	10mm +/-1mm	
LL	3.5mm +/-1mm	
F	0.55mm +/-0.1mm	

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	500	

General Information		
Supplier:	KEMET	
Series:	C900AH SFTY X1-400 Y1-250	
Style:	Radial Disc	
RoHS:	Yes	
Termination:	Tin	
Failure Rate:	N/A	
Qualifications:	UL, ENEC, VDE, CSA, CAN	
Halogen Free:	Yes	

Specifications		
Capacitance:	2200 pF	
Capacitance Tolerance:	20%	
Voltage AC:	400 VAC (X1), 250 VAC (Y1)	
Dielectric Withstanding Voltage:	4000 VDC	
Temperature Range:	-40/+125°C	
Temperature Coefficient:	Y5V	
Dissipation Factor:	5.00%	
Insulation Resistance:	10 GOhms	
Safety Class:	X1/Y1	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

