

**KEMET Part Number: PHE450MR7220JR06L2**  
(F450RM225J630Z)



Capacitor, Film, Double Metallized Polypropylene, 2.2 uF, +/-5% Tol, -55/+105C, General Purpose, 630 VDC@85C, Lead Spacing=37.5 mm



General Information	
Supplier:	KEMET
Dielectric:	Double Metallized Polypropylene
Application:	General Purpose
Sub Application:	DC or AC applications
Style:	Radial Box
Lead Form:	Wire Leads
Features:	Pulse
RoHS:	Yes

Dimensions (mm)		
Symbol	Dimension	Tolerance
L	41	MAX
H	36	MAX
T	19	MAX
S	37.5	+/-0.4
LL	18.5	+0.5
G	0.5	NOM
F	1	+/-0.05

Specifications	
Capacitance:	2.2 uF
Voltage:	630 VDC
Tolerance:	+/-5%
Voltage AC:	400 VAC
Voltage:	466.2 VDC (105C)
Rated Temperature:	85C
Temperature Range:	-55/+105C
Dissipation Factor @ 1 kHz:	0.03%
Insulation Resistance:	13.64 GOhm
Inductance:	6
Maximum dVdT:	700 v/us
Miscellaneous:	The Rated Voltage Decreases 1.3%/C Between +85C And +105C
Miscellaneous:	Rthha= 20 C/W (85C), 0.2 m/s

Packaging Specifications	
Package Kind:	Pizza
Package Quantity:	91

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006-2016 IntelliData.net