
KEMET Part Number: PHE450XD5220JD20R06L2

(F450DW223J3K0Z)



Capacitor, Film, Double Metallized Polypropylene, 0.022 uF, +/-5% Tol, -55/+105C, General Purpose, 3000 VDC@85C, Lead Spacing=22.5 mm



| Dimensions (mm) | | | |
|-----------------|-----------|-----------|--|
| Symbol | Dimension | Tolerance | |
| L | 26 | MAX | |
| Н | 23 | MAX | |
| Т | 13.5 | MAX | |
| S | 22.5 | +/-0.4 | |
| LL | 18.5 | +0.5 | |
| G | 0.5 | NOM | |
| F | 0.8 | +/-0.05 | |

| Packaging Specifications | | |
|--------------------------|-------|--|
| Package Kind: | Pizza | |
| Package Quantity: | 209 | |

| General Information | | |
|---------------------|---------------------------------|--|
| Supplier: | KEMET | |
| Dielectric: | Double Metallized Polypropylene | |
| Application: | General Purpose | |
| Sub Application: | DC or AC applications | |
| Style: | Radial Box | |
| Lead Form: | Wire Leads | |
| Features: | Pulse | |
| RoHS: | Yes | |

| Specifications | | |
|------------------------------|-----------------------------------------------------------------|--|
| Capacitance: | 0.022 uF | |
| Voltage: | 3000 VDC | |
| Tolerance: | +/-5% | |
| Voltage AC: | 1000 VAC | |
| Voltage: | 2220 VDC (105C) | |
| Rated Temperature: | 85C | |
| Temperature Range: | -55/+105C | |
| Dissipation Factor @ 1 kHz: | 0.03% | |
| Dissipation Factor @ 10 kHz: | 0.04% | |
| Dissipation Factor @ 100kHz: | 0.15% | |
| Insulation Resistance: | 1363.64 GOhm | |
| Inductance: | 6 | |
| Maximum dVdT: | 1800 v/us | |
| Miscellaneous: | The Rated Voltage Decreases 1.3%/C Between +85C And +105C | |
| Miscellaneous: | Rthha= 38 C/W (85C), 0.2 m/s | |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

