
KEMET Part Number: PME271YC5330MR30

(P272CE333M300A)



Capacitor, Film, Metallized Paper, 0.033 uF, +/-20% Tol, -40/+115C, Safety: Y2, 300 VAC, Lead Spacing=20.3 mm



Supplier:	KEMET
Dielectric:	Metallized Paper
Application:	Safety: Y2
Style:	Radial Molded
Lead Form:	Wire Leads
Features:	Pulse
Approvals:	ENEC,UL,cUL,CQC
RoHS:	Yes

General Information

Dimensions (mm)		
Symbol	Dimension	Tolerance
L	24	MAX
Н	14	MAX
Т	7.6	MAX
S	20.3	+/-0.4
LL	30	+5
F	0.8	+/-0.05

Specifications	
Capacitance:	0.033 uF
Voltage:	1000 VDC
Tolerance:	+/-20%
Voltage AC:	300 VAC
Rated Temperature:	115C
Temperature Range:	-40/+115C
Dissipation Factor @ 1 kHz:	1.3%
Insulation Resistance:	12 GOhm
Maximum dVdT:	1000 v/us
Miscellaneous:	SRF= 7 MHz

Packaging Specifications	
Package Kind:	Bulk
Package Quantity:	250

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

