

KEMET Part Number: R75LI32204000K
(R75L13220400-K)



Capacitor, Film, Metallized Polypropylene, 0.22 uF, +/-10% Tol, -55/+105C, General Purpose, 560 VDC@85C, Lead Spacing=15 mm



General Information	
Supplier:	KEMET
Brand:	Arcotronics
Dielectric:	Metallized Polypropylene
Application:	General Purpose
Sub Application:	Pulse
Style:	Radial Box
Lead Form:	Wire Leads
Features:	Pulse
RoHS:	Yes

Dimensions (mm)		
Symbol	Dimension	Tolerance
L	18	+0.5
H	14.5	+0.1
T	8.5	+0.2
S	15	+/-0.4
LL	30	+5
F	0.8	+/-0.05

Specifications	
Capacitance:	0.22 uF
Voltage:	560 VDC
Tolerance:	+/-10%
Voltage AC:	250 VAC
Voltage:	336 VDC (105C)
Rated Temperature:	85C
Temperature Range:	-55/+105C
Dissipation Factor @ 1 kHz:	0.05%
Dissipation Factor @ 10 kHz:	0.08%
Insulation Resistance:	100 GOhm
Inductance:	10
Maximum dVdT:	500 v/us

Packaging Specifications	
Package Kind:	Bulk
Package Type:	Bag
Package Quantity:	500

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006-2016 IntelliData.net