
## KEMET Part Number: R75MI33304030J

(75MI33304030J)



Capacitor, Film, Metallized Polypropylene, 0.33 uF, +/-5% Tol, -55/+105C, General Purpose, 400 VDC@85C, Lead Spacing=15 mm



General Information		
KEMET		
Metallized Polypropylene		
General Purpose		
AEC-Q200		
Radial Box		
Wire Leads		
Pulse		
AEC-Q200		
Yes		

Dimensions (mm)			
Symbol	Dimension	Tolerance	
L	18	+0.5	
Н	16	+0.1	
Т	10	+0.2	
S	15	+/-0.4	
LL	30	+5	
F	0.8	+/-0.05	

Specifications		
Capacitance:	0.33 uF	
Voltage:	400 VDC	
Tolerance:	+/-5%	
Voltage AC:	220 VAC	
Rated Temperature:	85C	
Temperature Range:	-55/+105C	
Dissipation Factor @ 1 kHz:	0.05%	
Dissipation Factor @ 10 kHz:	0.08%	
Insulation Resistance:	100 GOhm	
Inductance:	10	
Maximum dVdT:	900 v/us	
Miscellaneous:	Above 85C DC And AC Voltage Derating Is 1.25%/C	

Packaging Specifications		
Package Kind:	Bulk	
Package Quantity:	500	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

