

Capacitor, Tantalum, Radial, Solid Tantalum, Conformal, Dipped, 22 uF, +/-20% Tol, 16 V, Lead Spacing=2.54 mm



| Dimensions (mm) | | |
|-----------------|-----------|-----------|
| Symbol | Dimension | Tolerance |
| D | 6 | |
| H | 9.9 | |
| F | 0.5 | +/-0.05 |
| S | 2.54 | +/-0.38 |
| LL | 12.7 | +/-1.26 |

Notes:
 -Longest Lead Is Positive

| General Information | |
|------------------------|---|
| Supplier: | KEMET |
| Application: | General Purpose |
| Part Type Description: | Radial, Solid Tantalum, Conformal, Dipped |
| Body Type: | Radial |
| Termination Type: | Tin (Sn) |
| RoHS: | Yes |

| Specifications | |
|---------------------|-----------------------|
| Capacitance: | 22 uF |
| Tolerance: | +/-20% |
| Voltage: | 16 VDC (85C) |
| Voltage: | 12 VDC (125C Surge) |
| Voltage: | 0.16 V (125C Reverse) |
| Temperature Range: | -55/+125C |
| Leakage Current: | 2.6 uA |
| Dissipation Factor: | 6% |

| Packaging Specifications | |
|--------------------------|------|
| Package Kind: | Bulk |
| Package Type: | Bag |
| Package Quantity: | 50 |