
KEMET Part Number: T491D107K020AT

(B45196H4107K409)



Capacitor, Tantalum, SMD, MnO2, Molded, 100 uF, 7343, +/-10% Tol, -55/+125C, 20 VDC (85C)



Dimensions (mm)		
Symbol	Dimension	Tolerance
L	7.3	+/-0.3
W	4.3	+/-0.3
Н	2.8	+/-0.3
F	2.4	+/-0.1
S	1.3	+/-0.3
В	0.5	+/-0.15
Х	0.1	+/-0.1
Р	0.9	REF
R	1	REF
Т	0.13	REF
A	3.6	MIN
G	3.5	REF
E	3.5	REF

Packaging Specifications		
Package Kind:	T&R	
Package Size:	7 in/180 mm	
Package Quantity:	500	

General Information		
Supplier:	KEMET	
Application:	General Purpose	
Part Type Description:	SMD, MnO2, Molded	
Construction:	Standard Chip-MnO2	
Body Type:	SMD Chip	
Footprint:	7343	
Weight:	446.84 mg	
RoHS:	Yes	

Specifications		
Capacitance:	100 uF	
Tolerance:	+/-10%	
Voltage:	20 VDC (85C)	
Voltage:	13.4 VDC (125C)	
Temperature Range:	-55/+125C	
Current/Ripple Current:	408 mAmps (25C)	
Current/Ripple Current:	367.2 mAmps (85C)	
Current/Ripple Current:	163.2 mAmps (125C)	
Resistance/ESR:	0.9 Ohms (100kHz)	
Failure Rate:	N/A	
Leakage Current:	20 uA	
Dissipation Factor:	8%	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

