


Capacitor, Tantalum, SMD, Polymer, Molded, Face Down Terminals, 100 uF, 3216, +/-20% Tol, -55/+105C, 6.3 VDC (85C)



General Information	
Supplier:	KEMET
Application:	General Purpose
Sub Application:	(NonCombustibleCathode)
Part Type Description:	SMD, Polymer, Molded, Face Down Terminals
Construction:	Face Down Terminals-Polymer
Body Type:	SMD Chip
Footprint:	3216
Weight:	70.12 mg
RoHS:	Yes

Dimensions (mm)		
Symbol	Dimension	Tolerance
L	3.2	+/-0.2
W	1.6	+/-0.2
H	0.9	+/-0.1
F	1.2	+/-0.1
S	0.8	+/-0.2

Packaging Specifications	
Package Kind:	T&R
Package Size:	7 in/180 mm
Package Quantity:	3000

Specifications	
Capacitance:	100 uF
Tolerance:	+/-20%
Voltage:	6.3 VDC (85C)
Voltage:	5.04 VDC (105C)
Temperature Range:	-55/+105C
Current/Ripple Current:	775 mAmps (100kHz 45C)
Current/Ripple Current:	697.5 mAmps (85C)
Current/Ripple Current:	310 mAmps (105C)
Resistance/ESR:	100 mOhms (100kHz 25C)
Failure Rate:	N/A
Leakage Current:	63 uA
Dissipation Factor:	8%

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.