
KEMET Part Number: P295BL272M500A



P295, Film, Metallized Paper, Safety, 2700 pF, 20%, 500 VAC (Y1), 1500 VDC, 115C, Lead Spacing = 15mm



Dimensions	
L	18mm MAX
Н	14.5mm MAX
Т	7.5mm MAX
S	15mm +/-0.4mm
LL	30mm +5mm
F	0.8mm +/-0.05mm
G	0.5mm NOM

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	400	

General Information		
Supplier:	KEMET	
Series:	P295	
Dielectric:	Metallized Paper	
Style:	Radial	
Features:	EMI Safety	
RoHS:	Yes	
Lead:	Wire Leads	
Qualifications:	ENEC, UL, cUL, CQC, AEC- Q200	
AEC-Q200:	Yes	
Miscellaneous:	SRF= 30 MHz	

Specifications	
Capacitance:	2700 pF
Capacitance Tolerance:	20%
Voltage AC:	500 VAC (Y1)
Voltage DC:	1500 VDC
Temperature Range:	-40/+115C
Rated Temperature:	115C
Dissipation Factor:	1.30% 1kHz
Insulation Resistance:	12 GOhms
Max dV/dt:	2000 V/us
Safety Class:	Y1

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

