


Film, Metallized Polypropylene, AC Filter, C44H, 100 uF, 5%, 700 V, 330 V



**Dimensions**

<b>D</b>	65mm +/-0.5mm
<b>L</b>	98mm +/-2mm
<b>S</b>	22.5mm +/-1mm

**Packaging Specifications**

<b>Mounting:</b>	Bolt - M12x12.5
<b>Packaging:</b>	Bulk
<b>Packaging Quantity:</b>	9

**General Information**

<b>Dielectric:</b>	Metallized Polypropylene
<b>Style:</b>	Can
<b>Series:</b>	C44H
<b>Features:</b>	Single Phase PFC
<b>RoHS:</b>	Yes
<b>Lead:</b>	Fast On (2+2)
<b>Miscellaneous:</b>	Thermal Resistance = 8 C/W. Surge Voltage = 1050 VDC

**Specifications**

<b>Capacitance:</b>	100 uF
<b>Capacitance Tolerance:</b>	5%
<b>Voltage DC:</b>	700 VDC
<b>Voltage AC:</b>	330 VAC
<b>Temperature Range:</b>	-25/+70C
<b>Rated Temperature:</b>	70C
<b>Max dVdt:</b>	12.5 V
<b>Resistance:</b>	3.4 mOhms
<b>Current:</b>	25 Amps (RMS)
<b>Inductance:</b>	100 nH