


Film, Metallized Polypropylene, AC Filter, C44H, 600 uF, 5%, 700 V, 330 V



General Information

Dielectric:	Metallized Polypropylene
Style:	Can
Series:	C44H
Features:	Single Phase PFC
RoHS:	Yes
Lead:	Fast On (2+2)
Miscellaneous:	Thermal Resistance = 2.6 C/W. Surge Voltage = 1050 VDC

Dimensions

D	85mm +/-0.5mm
L	242mm +/-2mm
S	35mm +/-1mm

Packaging Specifications

Mounting:	Bolt - M12x16
Packaging:	Bulk
Packaging Quantity:	5

Specifications

Capacitance:	600 uF
Capacitance Tolerance:	5%
Voltage DC:	700 VDC
Voltage AC:	330 VAC
Temperature Range:	-25/+70C
Rated Temperature:	70C
Max dVdt:	12.5 V
Resistance:	1.9 mOhms
Current:	65 Amps (RMS)
Inductance:	180 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.