


3-TERMINAL POSITIVE VOLTAGE REGULATOR

LM7808

TO-220

Plastic Package



The Voltages available allow these Regulators to be used in Logic Systems, Instrumentation, Hi-Fi Audio Circuits and other Solid State Electronic Equipment

ABSOLUTE MAXIMUM RATINGS (T_a=25°C)

DESCRIPTION	SYMBOL	VALUE	UNIT
Input Voltage	V _{IN}	35	V
Power Dissipation at T _a =25°C	P _D	2	W
Power Dissipation at T _c =25°C	P _D	15	W
Operating Free Air, Case, or Virtual Junction Temperature Range	T _j	0 to +150	°C
Storage Temperature Range	T _{stg}	- 65 to +150	°C
Lead Temperature 1.6mm (1/16 inch) from Case for 10 seconds	T _L	260	°C

Recommended Operating Conditions

DESCRIPTION	SYMBOL	MIN	TYP	MAX	UNIT
Input Voltage	V _I	10.5		25	V
Output Current	I _O			1.5	A
Operating Junction Temperature	T _j	0		125	°C

ELECTRICAL CHARACTERISTICS (T_a=25°C unless specified otherwise)

V_{IN}=14V, I_O=500mA, T_a=25°C

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Output Voltage	V _O	25°C	7.7		8.3	V
		I _O =5mA ~ 1A V _{IN} =10.5 ~ 23V, P _D ≤ 15W, 0°C ~ 125°C	7.6		8.4	V
Line Regulation	R _{REGV}	V _{IN} =10.5 ~ 25V, 25°C			160	mV
		V _{IN} =11 ~ 17V, 25°C			80	mV
Ripple Rejection	R _R	V _{IN} =11.5 ~ 21.5V, f=120Hz, 0°C~125°C	55			dB
Load Regulation	R _{EGL}	I _O =5mA ~ 1.5A , 25°C			160	mV
		I _O =250mA ~ 750mA , 25°C			80	mV
Output Resistance	r _O	f=1KHz, 0°C~125°C		0.016		Ω
Temperature Coefficient of Output Voltage	ΔV _O /ΔT	I _O =5mA, 0°C~25°C		-0.8		mV/°C
Output Noise Voltage	V _{NO}	f=10Hz ~ 100KHz, 25°C		52		μV
Dropout Voltage	V _{DIF (min)}	I _O =1A , 25°C		2.0		V
Quiescent Current	I _Q	25°C			8.0	mA
Quiescent Current Change	ΔI _{QIN}	V _{IN} =10.5 ~ 25V, 0°C~150°C			1.0	mA
		I _O =5mA ~ 1A, 0°C~150°C			0.5	mA
Short Circuit Output Current	I _{SC}	25°C		450		mA
Peak Output Current	I _{omax}	25°C		2.2		A

Component Disposal Instructions

1. CDIL Semiconductor Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE).

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone + 91-11-2579 6150, 4141 1112 Fax + 91-11-2579 5290, 4141 1119

email@cdil.com www.cdilsemi.com