




**GenX3™ 600V IGBT**
**IXGH64N60A3  
IXGT64N60A3**
**Ultra-lowV<sub>sat</sub> PT IGBTs for up to  
5 kHz switching**


$$V_{CES} = 600V$$

$$I_{C110} = 64A$$

$$V_{CE(sat)} \leq 1.35V$$

| Symbol         | Test Conditions   | Maximum Ratings |            |
|----------------|---|-----------------|------------|
| $V_{CES}$      | $T_C = 25^\circ C$ to $150^\circ C$                       | 600             | V          |
| $V_{CGR}$      | $T_J = 25^\circ C$ to $150^\circ C$ , $R_{GE} = 1M\Omega$ | 600             | V          |
| $V_{GES}$      | Continuous  | $\pm 20$        | V          |
| $V_{GEM}$      | Transient   | $\pm 30$        | V          |
| $I_{C110}$     | $T_C = 110^\circ C$                                       | 64              | A          |
| $I_{CM}$       | $T_C = 25^\circ C$ , 1ms                                  | 400             | A          |
| <b>SSOA</b>    | $V_{GE} = 15V$ , $T_{VJ} = 125^\circ C$ , $R_G = 3\Omega$ | $I_{CM} = 100$  | A          |
| <b>(RBSOA)</b> | Clamped inductive load @ $\leq 600V$                      |                 |            |
| $P_C$          | $T_C = 25^\circ C$  | 460             | W          |
| $T_J$          |   | -55 ... +150    | $^\circ C$ |
| $T_{JM}$       |   | 150             | $^\circ C$ |
| $T_{stg}$      |   | -55 ... +150    | $^\circ C$ |
| $T_L$          | 1.6mm (0.062 in.) from case for 10s                       | 300             | $^\circ C$ |
| $T_{SOLD}$     | Plastic body for 10 seconds                               | 260             | $^\circ C$ |
| $M_d$          | Mounting torque (TO-247)                                  | 1.13/10         | Nm/lb.in.  |
| <b>Weight</b>  | TO-247  | 6               | g          |
|                | TO-268  | 5               | g          |

**TO-247 (IXGH)**

**TO-268 (IXGT)**


G = Gate      C = Collector  
E = Emitter    TAB = Collector

**Features**

- Optimized for low conduction losses
- Square RBSOA
- International standard packages

**Advantages**

- High power density
- Low gate drive requirement


**Applications**

- Power Inverters
- UPS
- Motor Drives
- SMPS
- PFC Circuits
- Battery Chargers
- Welding Machines
- Lamp Ballasts
- Inrush Current Protection Circuits

| Symbol        | Test Conditions                       | Characteristic Values |                     |              |
|---------------|---------------------------------------|-----------------------|---------------------|--------------|
|               |                                       | Min.                  | Typ.                | Max.         |
| $BV_{CES}$    | $I_C = 250\mu A$ , $V_{GE} = 0V$      | 600                   |                     | V            |
| $V_{GE(th)}$  | $I_C = 250\mu A$ , $V_{CE} = V_{GE}$  | 3.0                   |                     | 5.0 V        |
| $I_{CES}$     | $V_{CE} = V_{CES}$                    |                       |                     | 50 $\mu A$   |
|               | $V_{GE} = 0V$                         |                       | $T_J = 125^\circ C$ | 500 $\mu A$  |
| $I_{GES}$     | $V_{CE} = 0V$ , $V_{GE} = \pm 20V$    |                       |                     | $\pm 100$ nA |
| $V_{CE(sat)}$ | $I_C = 50A$ , $V_{GE} = 15V$ , Note 1 | 1.20                  | 1.35                | V            |

| Symbol       | Test Conditions  | Characteristic Values |      |              |
|--------------|--|-----------------------|------|--------------|
|              |  | Min.                  | Typ. | Max.         |
| $g_{fs}$     | $I_C = 50A, V_{CE} = 10V$ , Note 1   | 40                    | 70   | S            |
| $C_{ies}$    | $V_{CE} = 25V, V_{GE} = 0V, f = 1MHz$  |                       | 4850 | pF           |
| $C_{oes}$    |  |                       | 270  | pF           |
| $C_{res}$    |  |                       | 66   | pF           |
| $Q_g$        | $I_C = 50A, V_{GE} = 15V, V_{CE} = 0.5 \cdot V_{CES}$  |                       | 167  | nC           |
| $Q_{ge}$     |  |                       | 28   | nC           |
| $Q_{gc}$     |  |                       | 60   | nC           |
| $t_{d(on)}$  | <b>Inductive load, <math>T_J = 25^\circ C</math></b><br>$I_C = 50A, V_{GE} = 15V$<br>$V_{CE} = 480V, R_G = 3\Omega$  |                       | 26   | ns           |
| $t_{ri}$     |  |                       | 40   | ns           |
| $E_{on}$     |  |                       | 1.42 | mJ           |
| $t_{d(off)}$ |  |                       | 268  | ns           |
| $t_{fi}$     |  |                       | 222  | ns           |
| $E_{off}$    |  |                       | 3.28 | mJ           |
| $t_{d(on)}$  | <b>Inductive load, <math>T_J = 125^\circ C</math></b><br>$I_C = 50A, V_{GE} = 15V$<br>$V_{CE} = 480V, R_G = 3\Omega$ |                       | 25   | ns           |
| $t_{ri}$     |  |                       | 40   | ns           |
| $E_{on}$     |  |                       | 2.76 | mJ           |
| $t_{d(off)}$ |  |                       | 415  | ns           |
| $t_{fi}$     |  |                       | 362  | ns           |
| $E_{off}$    |  |                       | 6.00 | mJ           |
| $R_{thJC}$   |  |                       | 0.27 | $^\circ C/W$ |
| $R_{thCS}$   |  | 0.25                  |      | $^\circ C/W$ |


### TO-247 (IXGH) Outline



Terminals: 1 - Gate  
2 - Drain  
3 - Source  
Tab - Drain

| Dim.           | Millimeter |       | Inches |       |
|----------------|------------|-------|--------|-------|
|                | Min.       | Max.  | Min.   | Max.  |
| A              | 4.7        | 5.3   | .185   | .209  |
| A <sub>1</sub> | 2.2        | 2.54  | .087   | .102  |
| A <sub>2</sub> | 2.2        | 2.6   | .059   | .098  |
| b              | 1.0        | 1.4   | .040   | .055  |
| b <sub>1</sub> | 1.65       | 2.13  | .065   | .084  |
| b <sub>2</sub> | 2.87       | 3.12  | .113   | .123  |
| C              | .4         | .8    | .016   | .031  |
| D              | 20.80      | 21.46 | .819   | .845  |
| E              | 15.75      | 16.26 | .610   | .640  |
| e              | 5.20       | 5.72  | 0.205  | 0.225 |
| L              | 19.81      | 20.32 | .780   | .800  |
| L <sub>1</sub> |            | 4.50  |        | .177  |
| ∅P             | 3.55       | 3.65  | .140   | .144  |
| Q              | 5.89       | 6.40  | 0.232  | 0.252 |
| R              | 4.32       | 5.49  | .170   | .216  |
| S              | 6.15       | BSC   | 242    | BSC   |

### TO-268 (IXGT) Outline



| SYM            | INCHES |          | MILLIMETERS |          |
|----------------|--------|----------|-------------|----------|
|                | MIN    | MAX      | MIN         | MAX      |
| A              | .193   | .201     | 4.90        | 5.10     |
| A <sub>1</sub> | .106   | .114     | 2.70        | 2.90     |
| A <sub>2</sub> | .001   | .010     | 0.02        | 0.25     |
| b              | .045   | .057     | 1.15        | 1.45     |
| b <sub>2</sub> | .075   | .083     | 1.90        | 2.10     |
| C              | .016   | .026     | 0.40        | 0.65     |
| C <sub>2</sub> | .057   | .063     | 1.45        | 1.60     |
| D              | .543   | .551     | 13.80       | 14.00    |
| D <sub>1</sub> | .488   | .500     | 12.40       | 12.70    |
| E              | .624   | .632     | 15.85       | 16.05    |
| E <sub>1</sub> | .524   | .535     | 13.30       | 13.60    |
| e              |        | .215 BSC |             | 5.45 BSC |
| H              | .736   | .752     | 18.70       | 19.10    |
| L              | .094   | .106     | 2.40        | 2.70     |
| L <sub>1</sub> | .047   | .055     | 1.20        | 1.40     |
| L <sub>2</sub> | .039   | .045     | 1.00        | 1.15     |
| L <sub>3</sub> |        | .010 BSC |             | 0.25 BSC |
| L <sub>4</sub> | .150   | .161     | 3.80        | 4.10     |

Note 1: Pulse test,  $t \leq 300\mu s$ , duty cycle,  $d \leq 2\%$ .


### PRELIMINARY TECHNICAL INFORMATION

The product presented herein is under development. The Technical Specifications offered are derived from data gathered during objective characterizations of preliminary engineering lots; but also may yet contain some information supplied during a pre-production design evaluation. IXYS reserves the right to change limits, test conditions, and dimensions without notice.


IXYS reserves the right to change limits, test conditions and dimensions.

IXYS MOSFETs and IGBTs are covered 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 7,005,734 B2 7,157,338B2  
by one or more of the following U.S. patents: 4,850,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405 B2 6,759,692 7,063,975 B2  
4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2 7,071,537


**Fig. 1. Output Characteristics @ 25°C**




**Fig. 2. Extended Output Characteristics @ 25°C**




**Fig. 3. Output Characteristics @ 125°C**




**Fig. 4. Dependence of  $V_{CE(sat)}$  on Junction Temperature**




**Fig. 5. Collector-to-Emitter Voltage vs. Gate-to-Emitter Voltage**




**Fig. 6. Input Admittance**




**Fig. 7. Transconductance**




**Fig. 8. Gate Charge**




**Fig. 9. Capacitance**



**Fig. 10. Reverse-Bias Safe Operating Area**




**Fig. 11. Maximum Transient Thermal Impedance**




IXYS reserves the right to change limits, test conditions and dimensions.


**Fig. 12. Inductive Switching Energy Loss vs. Gate Resistance**




**Fig. 13. Inductive Switching Energy Loss vs. Junction Temperature**




**Fig. 14. Inductive Switching Energy Loss vs. Collector Current**




**Fig. 15. Inductive Turn-off Switching Times vs. Gate Resistance**




**Fig. 16. Inductive Turn-off Switching Times vs. Collector Current**




**Fig. 17. Inductive Turn-off Switching Times vs. Junction Temperature**




**Fig. 18. Inductive Turn-on  
Switching Times vs. Gate Resistance**



**Fig. 19. Inductive Turn-on  
Switching Times vs. Junction Temperature**



**Fig. 20. Inductive Turn-on  
Switching Times vs. Collector Current**





---

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).