

"MINI" AUTOMOTIVE FUSE CLIPS & HOLDERS

For .110 (2.8) × .032 (.80) MINI BLADE FUSES


For Littelfuse Mini 297 or 997 series/Bussmann ATM series or equivalent

VERTICAL FUSE ENTRY

Thru Hole Mount



- Low Profile



MATERIAL:


.016 (.41) thick Brass, Tin Plate
Current Rating: 30 Amps @ 500V AC

AVAILABLE ON TAPE AND REEL


Surface Mount




- Low Profile



Mounting Detail For Two Clips



Pad Layout For Two Clips



CAT. NO. 3564


CAT. NO. 3563 (Bulk)

CAT. NO. 3563TR (Tape & Reel)



Tape & Reel Spec's: 24mm wide; 12mm pitch; 13 inch reel (1500 pieces per reel)

SPECIFICATIONS

Material: .012 (.30) thick Brass, Tin Nickel Plate
Insulator: Glass filled Nylon, UL Rated 94V-0
Current Rating: 30 Amps @ 500V AC
Temperature Rating: -58°F to +292°F (-50°C to +145°C)



Mounting Detail For Two Clips



CAT. NO. 3544

CAT. NO. 3544-2

LOW PROFILE MINI FUSE HOLDER

For Littelfuse Low Profile Mini 897 series or equivalent


- Low insertion force
- Thru hole PC mountable, maintains position during wave soldering
- Fuse holder fully insulates clips to protect fuse from shorting
- Holder assures proper spacing and reduces assembly time

SPECIFICATIONS


Contacts: .016 (.41) thick Brass, Tin Nickel Plate
Insulator: PBT, UL Rated 94V-0
Current Rating: 20 Amps @ 500V AC
Temperature Rating: -58°F to +292°F (-50°C to +145°C)

MINI FUSE HOLDER

For Littelfuse Mini 297 or 997 series/Bussmann ATM or equivalents





Mounting Detail



Refer to page 35 for Cat. No. 3557 Clip details

Mounting Detail



CAT. NO. 3557-2


CAT. NO. 3568

HORIZONTAL FUSE ENTRY



For Littelfuse Mini 297 or 997 series/Bussmann ATM series or equivalent

SPECIFICATIONS

Contacts: .012 (.30) thick Brass, Tin Nickel Plate
Insulator: PBT, UL Rated 94V-0
Current Rating: 30 Amps @ 500V AC
Temperature Rating: -58°F to +292°F (-50°C to +145°C)



Mounting Detail For Two Clips



CAT. NO. 3549

CAT. NO. 3549-2

STANDARD AUTOMOTIVE BLADE FUSE CLIPS & HOLDERS

FOR .205 (5.2) × .025 (.64) STANDARD BLADE FUSES

For Littelfuse ATO 257 series/Bussmann ATC series or equivalent

- Thru hole PC mountable, maintains position during wave soldering
- Holder design prevents solder wicking
- Withstands the rigors of shock and vibration
- Holds fuse securely, even after multiple insertions

VERTICAL FUSE ENTRY


SPECIFICATIONS

Contacts: .016 (.41) thick Brass, Tin Nickel Plate



Insulator: Glass filled Nylon, UL Rated 94V-0

Current Rating: 30 Amps @ 500V AC

Temperature Rating: -58°F to +292°F (-50°C to +145°C)



Mounting Detail For Two Clips



CAT. NO. 3522-2

CAT. NO. 3522-3

CAT. NO. 3522

HORIZONTAL FUSE ENTRY

- Designed for low height clearance applications
- Fuse will be inserted parallel to board
- Thru hole PC mountable, maintains position during wave soldering
- Fuse holder fully insulates clips to protect fuse from shorting
- Holder assures proper spacing and reduces assembly time
- Polarized legs assure proper orientation of clips onto board


SPECIFICATIONS

Contacts: .012 (.30) thick Brass, Tin Nickel Plate



Insulator: PBT, UL Rated 94V-0

Current Rating: 30 Amps @ 500V AC

Temperature Rating: -58°F to +292°F (-50°C to +145°C)



Mounting Detail For Two Clips




CAT. NO. 3550-2

CAT. NO. 3550


2 IN 1 FUSE HOLDER

For Littelfuse ATO 257 series/Bussmann ATC series, Littelfuse Low Profile Mini 897 series or equivalents

- Accepts Standard Auto Fuses or Low Profile Mini Fuses
- Low insertion force
- Fuse holder fully insulates clips to protect fuse from shorting
- Holder assures proper spacing and reduces assembly time
- Thru hole PC mountable, maintains position during wave soldering



Mounting Detail



CAT. NO. 3557-2

SPECIFICATIONS

Contacts: .016 (.41) thick Brass, Tin Nickel Plate

Insulator: PBT, UL Rated 94V-0

Current Rating: 20 Amps @ 500V AC

Temperature Rating: -58°F to +292°F (-50°C to +145°C)


UNIVERSAL CLIP

For Littelfuse ATO 257 series/Bussmann ATC series, Littelfuse Mini 297 or 997 series/Bussmann ATM series, Littelfuse Low Profile Mini 897 series or equivalents



- Accepts most Auto-Blade Fuses
- Low insertion force
- Thru hole PC mountable, maintains position during wave soldering



Mounting Detail for Standard Auto Fuses and Low Profile Mini Fuse



Mounting Detail for Mini Fuse



SPECIFICATIONS

Contacts: .016 (.41) thick Brass, Tin Nickel Plate

Current Rating: 20 Amps @ 500V AC

CAT. NO. 3557