



**Step switch, 1p, Ie=25A, FS 0-1-2, 45°, maintained,  
48x48 mm, rear mounting**



*Powering Business Worldwide™*

**Part no. T3-1-8310/Z**  
**Article no. 215645**  
**Catalog No.**

### Delivery programme

Basic function  
 Basic function accessories

Busbar  
 Busbar for miniature circuit-breaker  
 Busbar for residual-current circuit-breakers  
 Busbar for combined residual-current/power circuit-breaker  
 Three-phase  
 EVG

Type  
 Product range

### Technical data ETIM 5.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)  
 Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar  
 (ecl@ss8-27-37-13-06 [ACN992007])

Number of phases		3
Suitable for number of devices		3
Pitch dimensions	mm	0
Cross section	mm <sup>2</sup>	10
Length	mm	157
Rated permanent current I <sub>u</sub>	A	63
Type of electric connection		Fork
Insulated		Yes
Rated surge voltage	kV	4
Conditioned rated short-circuit current I <sub>q</sub>	kA	25
Max. rated operation voltage U <sub>e</sub>	V	500
Rated short-time withstand current I <sub>cw</sub>	kA	0
Suitable for devices with N-busbar		No
Suitable for devices with auxiliary switch		No