



## Restarting device-set, 24-48VDC, 6HP

**Part no.** Z-FW-LPD/MO  
**Article no.** 290172  
**Catalog No.** Z-FW-LPD/MO

Similar to illustration

### Delivery programme

Basic function			Accessories for miniature circuit breaker Accessories for residual current circuit breakers
Basic function accessories			Restarting device
Application			Switchgear for industrial and commercial applications
Product range			Accessory
Side mounting			for fitting on right to: CLS6, PFIM, PFHM-4p, dRCM, Z-A40, PFR, Z-MS

### Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	$I_n$	A	0
Heat dissipation per pole, current-dependent	$P_{vid}$	W	0
Equipment heat dissipation, current-dependent	$P_{vid}$	W	0
Static heat dissipation, non-current-dependent	$P_{vs}$	W	0.8
Heat dissipation capacity	$P_{diss}$	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	40
			0

### Technical data ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary contact unit for distribution board (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ec@ss8.1-27-14-35-02 [AKE327010])			
Device fitting			Universal
Additional equipment			Monitoring unit with automatic reclosing
Attached at delivery			No
Assembly width (TE)			6
Number of normally open contacts			0
Number of normally closed contacts			0
Number of change-over contacts			0
Number of fault-signal switches			0
Rated switch current		A	0
Nominal rated voltage		V	48
Control voltage type			DC
With autotest for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			0
Suitable for max. current main contact unit		A	0